

Flood Risk Report

Quinnipiac Watershed, 01100004

Hartford County* and New Haven County*, Connecticut (Communities listed on next page)

*Spans more than one watershed. This report only covers a portion of the area within the studied watershed.

Report Number 02 **08/10/2015**

Draft - Preliminary





Project Area Community List

Community Name
Hartford County
City of Bristol
City of New Britain
Town of Plainville
Town of Southington
New Haven County
City of Ansonia
Town of Branford
Town of Cheshire
City of Derby
Town of East Haven
Town of Guilford
Town of Hamden
City of Meriden
City of Milford
City of New Haven
Town of North Branford
Town of North Haven
Town of Orange
Town of Prospect
Town of Wallingford
Town of Woodbridge

Community Name

Preface

The Department of Homeland Security (DHS), Federal Emergency Management Agency's (FEMA) Risk Mapping, Assessment, and Planning (Risk MAP) program provides states, tribes, and local communities with flood risk information and tools that they can use to increase their resilience to flooding and better protect their citizens. By pairing accurate floodplain maps with risk assessment tools and planning and outreach support, Risk MAP has transformed traditional flood mapping efforts into an integrated process of identifying, assessing, communicating, planning for, and mitigating flood-related risks.

This Flood Risk Report (FRR) provides non-regulatory information to help local or tribal officials, floodplain managers, planners, emergency managers, and others better understand their flood risk, take steps to mitigate those risks, and communicate those risks to their citizens and local businesses.

Because flood risk often extends beyond community limits, the FRR provides flood risk data for the entire Flood Risk Project as well as for each individual community. This also emphasizes that flood risk reduction activities may impact areas beyond jurisdictional boundaries.

Flood risk is always changing, and there may be other studies, reports, or sources of information available that provide more comprehensive information. The FRR is not intended to be regulatory or the final authoritative source of all flood risk data in the project area. Rather, it should be used in conjunction with other data sources to provide a comprehensive picture of flood risk within the project area.

Table of Contents

Pı	oject	Area	Community List	i
1	In	trodu	ction	1
	1.1	Abo	out Flood Risk	1
	1.	1.1	Calculating Flood Risk	1
	1.	1.2	Risk MAP Flood Risk Products	1
	1.2	Use	es of this Report	2
	1.3	Sou	rces of Flood Risk Assessment Data Used	3
	1.4	Rel	ated Resources	4
2	Fl	ood R	Risk Analysis	6
	2.1	Ove	erview	6
	2.2	Ana	alysis of Risk	6
	2.	2.1	Changes Since Last FIRM	6
	2.	2.2	Flood Depth and Analysis Grids	8
	2.	2.3	Estimated Flood Loss Information	9
	2.	2.4	Areas of Mitigation Interest	11
3	Fl	ood R	Risk Analysis Results	20
	3.1	Flo	od Risk Map	21
	3.2	Qui	innipiac Watershed Flood Risk Project Area Summary	23
	3.	2.1	Overview	23
	3.	2.2	Flood Risk Datasets	24
	3.3	Coı	nmunities	27
	3	3.1	City of Bristol Summary (CID 090023)	27
	3	3.2	City of New Britain Summary (CID 090032)	31
	3	3.3	Town of Plainville Summary (CID 090034)	36
	3	3.4	Town of Southington Summary (CID 090037)	41
	3	3.5	City of Ansonia Summary (CID 090071)	46
	3	3.6	Town of Branford Summary (CID 090073)	51
	3	3.7	Town of Cheshire Summary (CID 090074)	56
	3	3.8	City of Derby Summary (CID 090075)	61
	3	3.9	Town of East Haven Summary (CID 090076)	66
	3.	3.10	Town of Guilford Summary (CID 090077)	71

	3.3.11	Town of Hamden Summary (CID 090078)	76
	3.3.12	City of Meriden Summary (CID 090081)	80
	3.3.13	City of Milford Summary (CID 090082)	85
	3.3.14	City of New Haven Summary (CID 090084)	90
	3.3.15	Town of North Branford Summary (CID 090085)	95
	3.3.16	Town of North Haven Summary (CID 090086)	99
	3.3.17	Town of Orange Summary (CID 090087)	104
	3.3.18	Town of Wallingford Summary (CID 090090)	109
	3.3.19	Town of Prospect Summary (CID 090151)	114
	3.3.20	Town of Woodbridge Summary (CID 090153)	119
4	Actions	to Reduce Flood Risk	123
	4.1 Typ	bes of Mitigation Actions	124
	4.1.1	Preventative Measures	124
	4.1.2	Property Protection Measures	124
	4.1.3	Natural Resource Protection Activities	125
	4.1.4	Structural Mitigation Projects	125
	4.1.5	Public Education and Awareness Activities	125
	4.1.6	Emergency Service Measures	126
	4.2 Idea	ntifying Specific Actions for Your Community	127
	4.3 Mit	igation Programs and Assistance	128
	4.3.1	FEMA Mitigation Programs and Assistance	128
	4.3.2	Additional Mitigation Programs and Assistance	
5	Acrony	ms and Definitions	130
	5.1 Acr	onyms	130
	5.2 Def	initions	131
6	Additio	nal Resources	134
7	Data He	sed to Develop Flood Risk Products	136

FLOOD RISK REPORT

1 Introduction

1.1 About Flood Risk

Floods are naturally occurring phenomena that can and do happen almost anywhere. In its most basic form, a flood is an accumulation of water over normally dry areas. Floods become hazardous to people and property when they inundate an area where development has occurred, causing losses. Mild flood losses may have little impact on people or property, such as damage to landscaping or the generation of unwanted debris. Severe flooding can destroy buildings, ruin crops, and cause critical injuries or death.

Flooding is a natural part of our world and our communities.
Flooding becomes a significant hazard, however, when it intersects with the built environment.

1.1.1 Calculating Flood Risk

It is not enough to simply identify where flooding may occur. Just because one knows where a flood occurs does not mean he knows the **risk** of flooding. The most common method for determining flood risk, also referred to as vulnerability, is to identify the probability of flooding and the consequences of flooding. In other words:

Flood Risk (or Vulnerability) = **Probability x Consequences**, where

Probability = the likelihood of occurrence
Consequences = the estimated impacts associated with the
 occurrence

The probability of a flood is the likelihood that a flood will occur. The probability of flooding can change based on physical, environmental, and/or contributing engineering factors. Factors affecting the probability that a flood will impact an area range from changing weather patterns to the existence of mitigation projects. The ability to assess the probability of a flood and the level of accuracy for that assessment are also influenced by modeling methodology advancements, better knowledge, and longer periods of record for the water body in question.

The consequences of a flood are the estimated impacts associated with the flood occurrence. Consequences relate to humans activities within an area and how a flood impacts the natural and built environments.

1.1.2 Risk MAP Flood Risk Products

Through Risk MAP, FEMA provides communities with updated Flood Insurance Rate Maps (FIRMs) and Flood Insurance Studies (FISs) that focus on the probability of floods and that show where flooding may occur as well as the calculated 1-percent-annual-chance flood elevation.

Which picture below shows more flood risk?





Even if you assume that the flood in both pictures was the same probability—let's say a 10-percent-annual-chance flood—the consequences in terms of property damage and potential injury as a result of the flood in the bottom picture are much more severe. Therefore, the flood risk in the area shown in the bottom picture is higher.

The 1-percent-annual-chance flood, also known as the base flood, has a 1-percent chance of being equaled or exceeded in any given year. FEMA understands that flood risk is dynamic—that flooding does not stop at a line on a map—and as such, provides the following flood risk products:

- Flood Risk Report (FRR): The FRR presents key risk analysis data for the Flood Risk Project.
- Flood Risk Map (FRM): Like the example found in Section 3.1 of this
 document, the FRM shows a variety of flood risk information in the
 project area. More information about the data shown on the FRM
 may be found in Section 2 of this report.
- Flood Risk Database (FRD): The FRD is in GIS format and houses the flood risk data developed during the course of the flood risk analysis that can be used and updated by the community. After the Flood Risk Project is complete, this data can be used in many ways to visualize and communicate flood risk within the Flood Risk Project.

These Flood Risk Products provide flood risk information at both the Flood Risk Project level and community level (for those portions of each community within the Flood Risk Project). They demonstrate how decisions made within a Flood Risk Project can impact properties downstream, upstream, or both. Community-level information is particularly useful for mitigation planning and emergency management activities, which often occur at a jurisdictional level.

1.2 Uses of this Report

The goal of this report is to help inform and enable communities and tribes to take action to reduce flood risk. Possible users of this report include:

- Local elected officials
- Floodplain managers
- Community planners
- Emergency managers
- Public works officials
- Other special interests (e.g., watershed conservation groups, environmental awareness organizations, etc.)

State, local, and tribal officials can use the summary information provided in this report, in conjunction with the data in the FRD, to:

Update local hazard mitigation plans. As required by the 2000
Federal Stafford Act, local hazard mitigation plans must be updated
at least every five (5) years. Summary information presented in
Section 3 of this report and the FRM can be used to identify areas
that may need additional focus when updating the risk assessment



Whether or not an area might flood is one consideration. The extent to which it might flood adds a necessary dimension to that understanding.

section of a local hazard mitigation plan. Information found in Section 4 pertains to the different mitigation techniques and programs and can be used to inform decisions related to the mitigation strategy of local plans.

- Update community comprehensive plans. Planners can use flood risk information in the development and/or update of comprehensive plans, future land use maps, and zoning regulations. For example, zoning codes may be changed to better provide for appropriate land uses in high-hazard areas.
- Update emergency operations and response plans. Emergency
 managers can identify low-risk areas for potential evacuation and
 sheltering and can help first responders avoid areas of high-depth
 flood water. Risk assessment results may reveal vulnerable areas,
 facilities, and infrastructure for which planning for continuity of
 operations plans (COOP), continuity of government (COG) plans,
 and emergency operations plans (EOP) would be essential.
- Develop hazard mitigation projects. Local officials (e.g., planners and public works officials) can use flood risk information to reevaluate and prioritize mitigation actions in local hazard mitigation plans.
- Communicate flood risk. Local officials can use the information in this report to communicate with property owners, business owners, and other citizens about flood risks, changes since the last FIRM, and areas of mitigation interest. The report layout allows community information to be extracted in a fact sheet format.
- Inform the modification of development standards. Floodplain
 managers, planners, and public works officials can use information
 in this report to support the adjustment of development standards
 for certain locations. For example, heavily developed areas tend to
 increase floodwater runoff because paved surfaces cannot absorb
 water, indicating a need to adopt or revise standards that provide
 for appropriate stormwater retention.

The Flood Risk Database, Flood Risk Map, and Flood Risk Report are "non-regulatory" products. They are available and intended for community use but are neither mandatory nor tied to the regulatory development and insurance requirements of the National Flood Insurance Program (NFIP). They may be used as regulatory products by communities if authorized by state and local enabling authorities.

1.3 Sources of Flood Risk Assessment Data Used

To assess potential community losses, or the consequences portion of the "risk" equation, the following data is typically collected for analysis and inclusion in a Flood Risk Project:



Vulnerability of infrastructure is another important consideration.



Flooding along the Wabash River in Clark County, Illinois, contributed to a federal disaster declaration on June 24, 2008.

- Information about local assets or resources at risk of flooding
- Information about the physical features and human activities that contribute to that risk
- Information about where the risk is most severe

For most Flood Risk Projects, FEMA uses the following sources of flood risk information to develop this report:

- Hazus estimated flood loss information
- New engineering analyses (e.g., hydrology and hydraulic modeling) to develop new flood boundaries
- Locally supplied data (see Section 7 for a description)
- Sources identified during the Discovery process


1.4 Related Resources

For a more comprehensive picture of flood risk, FEMA recommends that state and local officials use the information provided in this report in conjunction with other sources of flood risk data, such as those listed below.

- FIRMs and FISs. This information indicates areas with specific flood hazards by identifying the limit and extent of the 1-percent-annual-chance floodplain and the 0.2-percent-annual-chance floodplain. FIRMs and FIS Reports do not identify all floodplains in a Flood Risk Project. The FIS Report includes summary information regarding other frequencies of flooding, as well as flood profiles for riverine sources of flooding. In rural areas and areas for which flood hazard data are not available, the 1-percent-annual-chance floodplain may not be identified. In addition, the 1-percent-annual-chance floodplain may not be identified for flooding sources with very small drainage areas (less than 1 square mile).
- Hazus Flood Loss Estimation Reports. Hazus can be used to generate reports, maps, and tables on potential flood damage that can occur based on new/proposed mitigation projects or future development patterns and practices. Hazus can also run specialized risk assessments, such as what happens when a dam or levee fails. Flood risk assessment tools are available through other agencies as well, including the National Oceanic and Atmospheric Administration (NOAA) and the U.S. Army Corps of Engineers (USACE). Other existing watershed reports may have a different focus, such as water quality, but may also contain flood risk and risk assessment information. See Section 6 for additional resources.
- Flood or multi-hazard mitigation plans. Local hazard mitigation plans include risk assessments that contain flood risk information and mitigation strategies that identify community priorities and







FEMA data can be leveraged to identify and measure vulnerability by including local building information (i.e. building type). The examples above show various ways to display flooding intersecting with buildings.

- actions to reduce flood risk. This report was informed by any existing mitigation plans in the Flood Risk Project.
- FEMA Map Service Center (MSC). The MSC has useful information, including fly sheets, phone numbers, data, and so forth. Letters of Map Change are also available through the MSC. The user can view FIRM databases and the National Flood Hazard Layer (NFHL) Database.

2 Flood Risk Analysis

2.1 Overview

Flood hazard identification uses FIRMs, and FIS Reports identify where flooding can occur along with the probability and depth of that flooding. Flood risk assessment is the systematic approach to identifying how flooding impacts the environment. In hazard mitigation planning, flood risk assessments serve as the basis for mitigation strategies and actions by defining the hazard and enabling informed decision making. Fully assessing flood risk requires the following:

- Identifying the flooding source and determining the flood hazard occurrence probability
- Developing a complete profile of the flood hazard including historical occurrence and previous impacts
- Inventorying assets located in the identified flood hazard area
- Estimating potential future flood losses caused by exposure to the flood hazard area

Flood risk analyses are different methods used in flood risk assessment to help quantify and communicate flood risk. Flood risk analysis can be performed on a large scale (state or community) level and on a very small scale (parcel or census block). Advantages of large-scale flood risk analysis, especially at the watershed level, include identifying how actions and development in one community can affect areas up- and downstream. On the parcel or census block level, flood risk analysis can provide actionable data to individual property owners so they can take appropriate mitigation steps.



2.2 Analysis of Risk

The FRR, FRM, and FRD contain a variety of flood risk analysis information to help describe and visualize flood risk within the project area. Depending on the scope of the Flood Risk Project for this project area, this information may include some or all of the following elements:

- Changes Since Last FIRM
- Water Surface, Flood Depth, and Analysis Grids
- Flood Risk Assessment Information
- Areas of Mitigation Interest

2.2.1 Changes Since Last FIRM

The Changes Since Last FIRM (CSLF) dataset, stored in the FRD and shown in Section 3 of this report, illustrates where changes to flood risk

State and Local Hazard Mitigation Plans are required to have a comprehensive all-hazard risk assessment. The flood risk analyses in the FRR, FRM, and FRD can inform the flood hazard portion of a community's or state's risk assessment. Further, data in the FRD can be used to develop information that meets the requirements for risk assessments as it relates to the hazard of flood in hazard mitigation plans.

may have occurred since the last FIRM was published for the subject area. Communities can use this information to update their mitigation plans, specifically quantifying "what is at risk" and identifying possible mitigation activities.

The CSLF dataset identifies changes in the Special Flood Hazard Area (SFHA) and floodway boundary changes since the previous FIRM was developed. These datasets quantify land area increases and decreases to the SFHA and floodway, as well as areas where the flood zone designation has changed (e.g., Zone A to AE, AE to VE, shaded Zone X protected by levee to AE for de-accredited levees).


The CSLF dataset is created in areas that were previously mapped using digital FIRMs. The CSLF dataset for this project area includes:

- Floodplain and/or Floodway Boundary Changes: Any changes to the existing floodplain or floodway boundaries are depicted in this dataset
- Floodplain Designation Changes: This includes changed floodplain designations (e.g., Zone A to Zone AE)
- CSLF Information: Within this dataset additional information is provided to help explain the floodplain and floodway boundary changes shown on the FIRM. This information is stored as digital attributes within the CSLF polygons and may include some or all of the following:
 - Changes in peak discharges
 - o Changes to the modeling methodology (e.g., tide gage analysis)
 - o New flood control structures (e.g., dams, levees, etc.)
 - o Changes to hydraulic structures (e.g., bridges, culverts, etc.)
 - o Sedimentation and/or erosion
 - Man-made changes to a watercourse (e.g., realignment or improvement)

It should be noted that reasons for the floodplain and floodway changes (also known as Contributing Engineering Factors) are intended to give the user a general sense of what caused the change, as opposed to providing a reason for each and every area of change.

- Count of Affected Structures: The total estimated count of affected buildings within the area of change. The data is only made available because the local jurisdiction was able to provide accurate building footprint data indicating the location of structures in and adjacent to the identified floodplains).
- Count of Affected Population: The total estimated affected population within the area of change. The data is only made





Floodplain maps have evolved considerably from the older paper-based FIRMs to the latest digital products and datasets.

CSLF data can be used to communicate changes in the physical flood hazard area (size, location) as part of the release of new FIRMS. It can also be used in the development or update of hazard mitigation plans to describe changes in hazard as part of the hazard profile.

CSLF data is shown in the FRR, and underlying data is stored in the FRD.

available because the local jurisdiction was able to provide population data that accompanied the structure data noted above.


2.2.2 Flood Depth and Analysis Grids


Grids are FEMA datasets provided in the FRD to better describe the risk of the flood hazard. While the FIRM and FIS Report describe "what" is at risk by identifying the hazard areas, water surface, flood depth, and analysis grids can help define "how bad" the risk is within those identified areas. These grids are intended to be used by communities for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. Grids provided in the FRD for this project area include the following:

• Flood Depth Grids (for the calculated flood frequencies included in the FIS Report): Flood Depth Grids are created for each flood frequency calculated during the course of a Flood Risk Project. These grids communicate flood depth as a function of the difference between the calculated water surface elevation and the ground. Four grids will normally be delivered for riverine areas for the standard flood frequencies (10-, 4-, 2-, 1-, and 0.2-percentannual-chance). Coastal areas only receive the 1-percent-annual-chance grid.

Depth grids form the basis for refined Hazus loss estimates (as presented in a table in Section 3 of this report) and are used to calculate potential flood losses for display on the FRM and for tabular presentation in this report. Depth grids may also be used for a variety of ad-hoc risk visualization and mitigation initiatives.

- Percent Annual Chance of Flooding Grid: This is a grid dataset that represents the percent annual chance of flooding for locations along a flooding source. This grid uses the four standard flood frequencies.
- Percent 30-Year Chance of Flooding Grid: This is a grid dataset that
 represents the estimated likelihood of flooding at least once within
 a 30-year period, which is the average lifespan for a home
 mortgage, for all locations within the extent of the 1-percentannual-chance and 0.2-percent-annual-chance floodplain.
- Water-Surface Elevation Change Grid: This dataset provides the ability to see vertical changes in the water-surface elevation between the existing FIRM and the revised FIRM. This dataset would be the equivalent of the CSLF dataset, but as a vertical analysis as opposed to a horizontal analysis since last FIRM.
- Water-Surface Elevation Grids: This dataset represents the raw results of the hydrologic and hydraulic analysis before adjustments are made to account for influences associated with other flooding sources.





Grid data can make flood mapping more informative. The top image is a flood depth grid showing relative depths of water in a scenario flood event. The bottom image is a percent annual chance of flooding grid, which shows inundation areas of various frequency floods.

Grid data can be used to communicate the variability of floodplains, such as where floodplains are particularly deep or hazardous, where residual risks lie behind levees, and where losses may be great after a flood event. For mitigation planning, grid data can inform the hazard profile and vulnerability analysis (what is at risk for different frequencies) and can be used for preliminary benefit-cost analysis screening. For floodplain management, higher regulatory standards can be developed in higher hazard flood prone areas (i.e., 10-percent-chance floodplains or deep floodplains).

Grid data is stored in the FRD, and a list of available grid data is provided in the FRR. Visualizations of grids (maps) are not provided.

2.2.3 Estimated Flood Loss Information

Flood loss estimates provided in the FRR were developed using a FEMA flood loss estimation tool, Hazus. Originally developed for earthquake risk assessment, Hazus has evolved into a multi-hazard tool developed and distributed by FEMA that can provide loss estimates for floods, earthquakes, and hurricane winds. Hazus is a nationally accepted, consistent flood risk assessment tool to assist individuals and communities to create a more accurate picture of flood risk. Some benefits of using Hazus include the following:

- Outputs that can enhance state and local mitigation plans and help screen for cost-effectiveness in FEMA mitigation grant programs
- Analysis refinement through updating inventory data and integrating data produced using other flood models
- Widely available support documents and networks (Hazus Users Groups)

Files from the FRD can be imported into Hazus to develop other risk assessment information including:

- Debris generated after a flood event
- Dollar loss of the agricultural products in a study region
- Utility system damages in the region
- Vehicle loss in the study region
- Damages and functionality of lifelines such as highway and rail bridges, potable water, and wastewater facilities

Scenario-Based Flood Loss Estimates:

Scenario-based flood losses have been calculated using Hazus for the 10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events. In this report, these losses are expressed in dollar amounts and are provided for the Flood Risk Project area only, even though results are shown for the entire watershed and at the local jurisdiction level.

Loss estimates are based on best available data, and the methodologies applied result in an approximation of risk. These estimates should be used to understand relative risk from flood and potential losses. Uncertainties are inherent in any loss estimation methodology, arising in part from approximations and simplifications that are necessary for a comprehensive analysis (e.g., incomplete inventories, demographics, or economic parameters).

Flood loss estimates are being provided at the project and community levels for multiple flood frequencies including:

 Residential Asset Loss: These include direct building losses (estimated costs to repair or replace the damage caused to the



Hazus is a loss estimation methodology developed by FEMA for flood, wind, and earthquake hazards. The methodology and data established by Hazus can also be used to study other hazards. Hazus is a loss estimation methodology developed by FEMA for flood, wind, and earthquake hazards. The methodology and data established by Hazus can also be used to study other hazards.

Hazus-estimated loss data can be used in many ways to support local decision making and explanation of flood risk. For mitigation planning purposes, loss data can be used to help meet requirements to develop loss information for the hazard of flood. Also, the FRM can show where flood risk varies by geographic location. For emergency management, Hazus data can help forecast losses based on predicted events, and resources can be assigned accordingly. Loss information can support floodplain management efforts, including those to adopt higher regulatory standards. Also, awareness of exposed essential facilities and infrastructure encourages mitigation actions to protect citizens from service disruption should flooding occur.

Hazus estimated loss data is summarized in the FRR and on the FRM and stored in the FRD.

- building) for all classes of residential structures including single family, multi-family, manufactured housing, group housing, and nursing homes. This value also includes content losses.
- Commercial Asset Loss: These include direct building losses for all classes of commercial buildings including retail, wholesale, repair, professional services, banks, hospitals, entertainment, and parking facilities. This value also includes content and inventory losses.
- Other Asset Loss: This includes losses for facilities categorized as industrial, agricultural, religious, government, and educational. This value also includes content and inventory losses.
- Essential Facility Losses: Essential facilities are defined in Hazus as
 facilities which provide services to the community and should be
 functional after a flood, including schools, police stations, fire
 stations, medical facilities, and emergency operation centers. These
 facilities would otherwise be considered critical facilities for
 mitigation planning purposes. Estimated damages (in terms of loss
 of function) for essential facilities are determined on a site-specific
 basis according to latitude and longitude. For this report, Hazus
 calculates the types and numbers of essential facilities impacted.
- Infrastructure: For analysis of infrastructure, Hazus supports the
 analysis of transportation systems and lifeline utility systems.
 Transportation systems include highways, railways, light railways,
 busses, ports and harbors, ferries, and airport systems. Utility
 systems include potable water systems, wastewater, oil, natural gas,
 electric power, and communication systems. For this report, Hazus
 calculates the types of infrastructure impacted.
- Business Disruption: This includes the losses associated with the
 inability to operate a business due to the damage sustained during
 the flood. Losses include inventory, income, rental income, wage,
 and direct output losses, as well as relocation costs.
- Annualized Losses: Annualized losses are calculated using Hazus by taking losses from multiple events over different frequencies and expressing the long-term average by year. This factors in historic patterns of frequent smaller floods with infrequent but larger events to provide a balanced presentation of flood damage.
- Loss Ratio: The loss ratio expresses the scenario losses divided by the total building value for a local jurisdiction and can be a gage to determine overall community resilience as a result of a scenario event. For example, a loss ratio of 5 percent for a given scenario would indicate that a local jurisdiction would be more resilient and recover more easily from a given event, versus a loss ratio of 75 percent which would indicate widespread losses. An annualized loss ratio uses the annualized loss data as a basis for computing the

ratio. Loss ratios are not computed for business disruption. These data are presented in the FRR.

 Hazus Flood Risk Value: On the FRM, flood risk is expressed in the following five categories: very low, low, medium, high, and very high for census blocks that have flood risk. It is based on the 1percent-annual-chance total asset loss by census block.

2.2.4 Areas of Mitigation Interest

Many factors contribute to flooding and flood losses. Some are natural, and some are not. In response to these risks, there has been a focus by the federal government, state agencies, and local jurisdictions to mitigate properties against the impacts of flood hazards so that future losses and impacts can be reduced. An area identified as an Area of Mitigation Interest (AoMI) is an important element of defining a more comprehensive picture of flood risk and mitigation activity in a watershed, identifying target areas and potential projects for flood hazard mitigation, encouraging local collaboration, and communicating how various mitigation activities can successfully reduce flood risk.

This report and the FRM may include information that focuses on identifying Areas of Mitigation Interest that may be contributing (positively or negatively) to flooding and flood losses in the Flood Risk Project. AoMIs are identified through coordination with local stakeholders; through revised hydrologic and hydraulic and/or coastal analyses; by leveraging other studies or previous flood studies; from community mitigation plans, floodplain management plans, and local surveys; and from the mining of federal government databases (e.g., flood claims, disaster grants, and data from other agencies). Below is a list of the types of Areas of Mitigation Interest that may be identified in this Flood Risk Report, shown on the Flood Risk Map, and stored in the Flood Risk Database:

Dams

A dam is a barrier built across a waterway for impounding water. Dams vary from impoundments that are hundreds of feet tall and contain thousands of acre-feet of water (e.g., Hoover Dam) to small dams that are a few feet high and contain only a few acre-feet of water (e.g., small residential pond). "Dry dams," which are designed to contain water only during floods and do not impound water except for the purposes of flood control, include otherwise dry land behind the dam.

While most modern, large dams are highly engineered structures with components such as impervious cores and emergency spillways, most smaller and older dams are not. State dam safety programs emerged in the 1960s, and the first Federal Guidelines for Dam Safety were not prepared until 1979. By this time, the vast majority of dams in the United States had already been constructed.



Dams vary in size and shape, the amount of water they impound, and their assigned hazard classification.

Reasons dams are considered AoMIs:

- Many older dams were not built to any particular standard and thus may not withstand extreme rainfall events. Older dams in some parts of the country are made out of an assortment of materials. These structures may not have any capacity to release water and could be overtopped, which could result in catastrophic failure.
- Even dams that follow current dam safety programs may not be regulated, as downstream risk may have changed since the dam was constructed. Years after a dam is built, a house, subdivision, or other development may be constructed in the area downstream of the dam. Thus, a subsequent dam failure could result in damage. Since these dams are not regulated, it is impossible to predict how safe they are.
- A significant dam failure risk is structural deficiencies associated with older dams that are not being adequately addressed today through needed inspection/maintenance practices.
- For larger dams a flood easement may have been obtained on a property. However, there may have been buildings constructed in violation of the flood easement.
- When a new dam is constructed, the placement of such a large volume of material in a floodplain area (if that is the dam location) will displace flood waters and can alter how the watercourse flows. This can result in flooding upstream, downstream, or both.
- ➤ For many dams, the dam failure inundation zone is not known. Not having knowledge of these risk areas could lead to unprotected development in these zones.

Levees and Major Embankments

FEMA defines a levee as "a man-made structure, usually an earthen embankment, designed and constructed in accordance with sound engineering practices to contain, control, or divert the flow of water so as to provide protection from temporary flooding." Levees are sometimes referred to as dikes. Soil used to construct a levee is compacted to make the levee as strong and stable as possible. To protect against erosion and scouring, levees can be covered with everything from grass and gravel to harder surfaces like stone (riprap), asphalt, or concrete.



This dam failure caused flooding that damaged several homes and vehicles.

Similar to dams, levees have not been regulated in terms of safety and design standards until relatively recently. Many older levees were constructed in a variety of ways, from a farmer piling dirt along a stream to prevent nuisance flooding to levees made out of old mining spoil material. As engineered structures, levees are designed to a certain height and can fail if a flood event is greater than anticipated.


A floodwall is a vertical wall that is built to provide protection from a flood in a similar manner as a levee. Typically made of concrete or steel, floodwalls often are erected in urban locations where there is not enough room for a levee. Floodwalls are sometimes constructed on a levee crown to increase the levee's height.

Most new dams and levees are engineered to a certain design standard. If that design is exceeded, they could be overtopped and fail catastrophically, causing more damage than if the levee was not there in the first place. Few levees anywhere in the nation are built to more than a 1-percent-annual-chance flood protection rating, and the areas behind them are still at some risk for flooding. This threat is called residual risk. In some states, residual risk areas can extend up to 15 miles from a riverbank. Although the probability of flooding may be lower because a levee exists, risk is nonetheless still present. The American Society of Civil Engineers' publication "So, You Live Behind a Levee!" provides an in-depth explanation of levee and residual risk.

Major embankments, on the other hand, are rarely designed with any flood protection level in mind. Railroads, road abutments, and canals—especially in the Western United States—are not considered levees or dams and have issues such as unknown construction materials/methods. These embankments are not regulated from a flood risk standpoint.

Reasons levees and major embankments are considered AoMIs:

- Like dams, many levees in the United States were constructed using unknown techniques and materials. These levees have a higher failure rate than those that have been designed to today's standards.
- ➤ A levee might not provide the flood risk reduction it once did as a result of flood risk changes over time. Flood risk can change due to a number of factors, including increased flood levels due to climate change or better estimates of flooding, development in the watershed increasing flood levels and settlement of the levee or floodwall, and sedimentation in the levee channel. Increased flood levels mean decreased flood protection. The lack of adequate maintenance over



For more information about the risks associated with living behind levees, consult the publication "So, You Live Behind a Levee!" published by the American Society of Civil Engineers at http://content.asce.org/ASC ELeveeGuide.html.





Canal levee breaches as a result of Hurricane Katrina in New Orleans in 2005. Note damages can be more extensive due in high velocity flood flows than if the levee was not there.

- time will also reduce the capability of a levee to contain the flood levels for which it was originally designed.
- Given enough time, any levee will eventually be overtopped or damaged by a flood that exceeds the levee's capacity. Still, a widespread public perception of levees is that they will always provide protection. This perception may lead to not taking mitigation actions such as purchasing flood insurance.
- A levee is a system that can fail due to its weakest point, and therefore maintenance is critical. Many levees in the United States are poorly maintained or not maintained at all. Maintenance also includes maintaining the drainage systems behind the levees so they can keep the protected area dry.

Coastal Structures

Coastal structures are used to "harden" the shoreline for a variety of purposes and include:

- o **Jetties:** Structures constructed to direct currents or accommodate vessels.
- Groynes: Protective structures of stone or concrete that extend from shore into the water to prevent a beach from washing away.
- Sea walls: A form of hard and strong coastal defense constructed on the inland part of a coast to reduce the effects of strong waves.

As the rate of sea level rise accelerates, an increase in coastal erosion is likely. We may now be facing rapid sea level changes on a scale of decades. Higher sea levels could affect the coastal zone and accelerate coastal erosion and flooding in a variety of ways, including greater shoreline retreat; increased coastal erosion rates; property destruction; and saltwater intrusion into bays, rivers, and underground water resources. In addition, a general elevation in the water table due to sea level rise will result.

o Reasons coastal structures are considered AoMIs:

While coastal structures or "hardening of the shoreline" may provide a temporary level of flood reduction for a very specific site, they also interrupt the dynamic processes of the littoral flow (flow along the coastline) which results in accelerated coastal erosion.



Severe beach erosion and damage resulting from a nor'easter.

- Erosion often occurs along beaches during storms, especially severe storms that stay offshore for days and result in ongoing battering of the shoreline through high wind and waves. As the beach erodes, vulnerable properties are placed at even greater risk to coastal flooding, storm surge, wave heights, wave run up, and coastal erosion.
- Higher water tables associated with sea level rise could lead to the failure of septic systems and other drainage systems, such as storm drains, which need to be located at a certain elevation above the water table. Elevation of the water table would also affect the river drainage systems by affecting the rate of infiltration and increasing the amount of runoff which would, in turn, increase the risk of flooding.

Stream Flow Constrictions

A stream flow constriction occurs when a human-made structure, such as a culvert or bridge, constricts the flow of a river or stream. The results of this constriction can be increased damage potential to the structure, an increase in velocity of flow through the structure, and the creation of significant ponding or backwater upstream of the structure. Regulatory standards regarding the proper opening size for a structure spanning a river or stream are not consistent and may be non-existent. Some local regulations require structures to pass a volume of water that corresponds to a certain size rain event; however, under-sizing these openings can result in flood damage to the structure itself. After a large flood event, it is not uncommon to have numerous bridges and culverts "washed out."

o Reasons stream flow constrictions are considered AoMIs:

- Stream flow constrictions can back water up on property upstream of the structure if not designed properly.
- These structures can accelerate the flow through the structure causing downstream erosion if not properly mitigated. This erosion can affect the structure itself, causing undermining and failure.
- ➤ If the constriction is a bridge or culvert, it can get washed out, causing an area to become isolated and potentially more difficult to evacuate.
- Washed-out culverts and associated debris can wash downstream and cause additional constrictions.

At-Risk Essential Facilities

Essential facilities, sometimes called "critical facilities," are those whose impairment during a flood could cause significant problems to individuals or communities. For example, when a community's wastewater treatment is flooded and shut down, not only do contaminants escape and flow into the floodwaters, but backflows of sewage can contaminate basements or other areas of the community. Similarly, when a facility such as a hospital is flooded, it can result in a significant hardship on the community not only during the event but long afterwards as well.

o Reasons at-risk essential facilities are considered AoMIs:

- Costly and specialized equipment may be damaged and need to be replaced.
- Impairments to facilities such as fire stations may result in lengthy delays in responding and a focus on evacuating the facility itself.
- Critical records and information stored at these facilities may be lost.

Past Flood Insurance Claims and Individual Assistance/Public Assistance Hotspots

Assistance provided after flood events (flood insurance in any event and Individual Assistance [IA] or Public Assistance [PA] after declared disasters) occurs in flood affected areas. Understanding geographically where this assistance is being provided may indicate unique flood problems.

Flood insurance claims are not always equally distributed in a community. Although estimates indicate that 20 to 50 percent of structures in identified flood hazard areas have flood insurance, clusters of past claims may indicate where there is a flood problem. However, clusters of past claims and/or areas where there are high payments under FEMA's IA or PA Programs may indicate areas of significant flood hazard.

• Reasons past claim hotspots are considered AoMIs:

- A past claim hotspot may reflect an area of recent construction (large numbers of flood insurance policies as a result of a large number of mortgages) and an area where the as-built construction is not in accordance with local floodplain management regulations.
- Sometimes clusters of past claims occur in subdivisions that were constructed before flood protection standards were in place, places with inadequate



Clusters of past flood insurance claims can show where there is a repetitive flood problem.

- stormwater management systems, or in areas that may not have been identified as SFHAs.
- Clusters of IA or PA claims may indicate areas where high flood insurance coverage or other mitigation actions are needed.

• Areas of Significant Land Use Change

Development, whether it is a 100-lot subdivision or a single lot bigbox commercial outlet, can result in large amounts of fill and other material being deposited in flood storage areas, thereby increasing flood hazards downstream.

Additionally, when development occurs, hard surfaces such as parking lots, buildings and driveways do not allow water to absorb into the ground, and more of the rainwater becomes runoff flowing directly into streams. As a result, the "peak flow" in a stream after a storm event will be higher and will occur faster. Without careful planning, major land use changes can affect the impervious area of a site and result in a significant increase in flood risk caused by streams that cannot handle the extra storm water runoff.


Sometimes a major land use change may be for planning purposes only. For example, a land use change that rezones land from a classification such as floodplain that restricts development to a zone such as industrial or high density residential could result in significant new infrastructure and structures in high flood risk areas.

Reasons Areas of Significant Land Use Change are considered AoMIs:

- Development in areas in the SFHA reduces flood storage areas, which can make flooding worse at the development site and downstream of it.
- Impervious surfaces speed up the water flowing in the streams, which can increase erosion and the danger that fast-flowing floodwaters pose to people and buildings.
- Rezoning flood-prone areas to high densities and/or higher intensity uses can result in more people and property at risk of flooding and flood damage.

• Key Emergency Routes Overtopped During Frequent Flooding Events

Roads are not always elevated above estimated flood levels, and present a significant flood risk to motorists during flooding events. When alternate routes are available, risks may be reduced, including risks to life and economic loss.





Rooftops, pavements, patios, and driveways contribute to the impervious area in a watershed. This occurs in both urban areas and rural areas being developed.



When large highways close due to flooding, traffic is detoured causing inconvenience and economic loss.

• Reasons overtopped roads are considered AoMIs:

- Such areas, when identified, can be accounted for and incorporated into Emergency Action Plans.
- Roads may be elevated or reinforced to reduce the risk of overtopping during flood events.

Drainage or Stormwater-Based Flood Hazard Areas, or Areas Not Identified as Floodprone on the FIRM But Known to Be Inundated

Flood hazard areas exist everywhere. While FEMA maps many of these, others are not identified. Many of these areas may be located in communities with existing, older, and often inadequate stormwater management systems or in very rural areas. Other similar areas could be a result of complex or unique drainage characteristics. Even though they are not mapped, awareness of these areas is important so adequate planning and mitigation actions can be performed.

Reasons drainage or stormwater-based flood hazard areas or unidentified floodprone locations are considered AoMIs:

- So further investigation of such areas can occur and, based on scientific data, appropriate mitigation actions can result (e.g., land use and building standards).
- To create viable mitigation project applications in order to reduce flood losses.

• Areas of Mitigation Success

Flood mitigation projects are powerful tools to communicate the concepts of mitigation and result in more resilient communities. Multiple agencies have undertaken flood hazard mitigation actions for decades. Both structural measures—those that result in flood control structures—and non-structural measures have been implemented in thousands of communities. An extensive list of mitigation actions can be found in Section 4.

Reasons areas of mitigation success are considered AoMIs:

- Mitigation successes identify those areas within the community that have experienced a reduction or elimination of flood risk.
- Such areas are essential in demonstrating successful loss reduction measures and in educating citizens and officials on available flood hazard mitigation techniques.
- Avoided losses can be calculated and shown.

Areas of Significant Riverine or Coastal Erosion

Stream channels are shaped by a number of factors, including degradation, aggradation, general scour, local scour, deposition, and lateral migration. Streams are constantly progressing towards a state of dynamic equilibrium involving water and sediment.

Reasons why areas of significant riverine or coastal erosion are considered AoMIs:

- Riverine flood damage assessments generally consider inundation alone
- Bank erosion caused by within-channel flows is not recognized as a significant hazard in Federal floodplain management regulations
- Riverine and coastal erosion can undercut structures and roads, causing instability and possible collapse
- Landslides and mudslides are a result of erosion
- Approximately one-third of the nation's streams experience severe erosion problems

Other

Other types of flood risk areas include drainage or stormwaterbased flood hazard areas, or areas known to be inundated during storm events.

3 Flood Risk Analysis Results

The following pages provide summary flood risk results for the Flood Risk Project as follows:

- Flood Risk Map (FRM). Within the Flood Risk Project, the FRM displays base data reflecting community boundaries, major roads, and stream lines; potential losses that include both the 2010 Flood Average Annualized Loss (AAL) Study supplemented with new Hazus runs for areas with new or updated flood modeling; new Flood Risk Project areas; a bar chart summarizing community per capita loss; and graphics and text that promote access and usage of additional data available through the FRD, FIRM, and National Flood Hazard Layer and viewers (desktop or FEMA website, etc.). This information can be used to assist in Flood Risk Project-level planning as well as for developing mitigation actions within each jurisdiction located within the Flood Risk Project.
- Flood Risk Project Summary. Within the Flood Risk Project area, summary data for some or all of the following datasets are provided for the entire project area and also on a jurisdiction-by-jurisdiction basis:
 - Changes Since Last FIRM (CSLF). A summary of where the floodplain and flood zones have increased or decreased (only analyzed for areas that were previously mapped using digital FIRMs).
 - Flood Depth and Analysis Grids. A general discussion of the data provided in the FRD.
 - Flood Risk Assessment Information. A loss estimation of potential flood damages using different flood scenarios.
 - Areas of Mitigation Interest. A description of areas that may require mitigation or additional risk analysis.

The FRM provides a graphical overview of the Flood Risk Project which highlights areas of risk that should be noted, based on potential losses, exposed facilities, etc., based on data found in the FRD. Refer to the data in the FRD to conduct additional analyses.

3.1 Flood Risk Map

The Flood Risk Map for this Flood Risk Project will be shown below. In addition to this reduced version of the map, a full size version will be available within the FRD.

This page left intentionally blank.

3.2 Quinnipiac Watershed Flood Risk Project Area Summary

Quinnipiac Watershed encompasses three counties and 38 communities in Connecticut. This particular project affects two counties and 20 communities, focusing on flooding sources of particular importance to communities and/or gaps in the mapped floodplain. The other counties and communities in the watershed are not included in this analysis and have no updated SFHAs or BFEs. Flood-hazard data for the communities in this report are limited to the FIRM panel footprint of this project.

3.2.1 Overview

Quinnipiac Watershed, located in Connecticut, includes the following communities in this project:

Community Name	CID	Total Community Population ¹	Percent of Population in Project Area ²	Total Community Land Area (sq mi) ³	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Bristol	090023	60,062	1.0	26.5	2.3	Υ		
City of New Britain	090032	71,538	3.9	13.3	7.9	Υ		
Town of Plainville	090034	17,328	68.8	9.8	67.2	Υ		
Town of Southington	090037	39,728	78.4	36.0	58.2	Υ		
City of Ansonia	090071	18,554	17.9	6.0	23.9	Υ		
Town of Branford	090073	28,683	34.7	22.0	43.9	Υ		
Town of Cheshire	090074	28,543	65.9	32.9	62.3	Υ		
City of Derby	090075	12,391	21.0	5.0	21.2	Υ		
Town of East Haven	090076	28,189	72.5	12.3	76.1	Υ		
Town of Guilford	090077	21,398	0.1	47.1	1.5	Υ		
Town of Hamden	090078	56,913	74.2	32.8	67.9	Υ		
City of Meriden	090081	58,244	34.5	23.7	46.7	Υ		
City of Milford	090082	52,305	26.6	22.6	42.1	Υ		
City of New Haven	090084	123,626	23.0	18.8	17.0	Υ		
Town of North Branford	090085	13,906	89.2	24.9	82.4	Υ		
Town of North Haven	090086	23,035	100	20.8	98.0	Υ		
Town of Orange	090087	13,233	58.7	17.2	59.6	Υ		
Town of Wallingford	090090	43,026	74.5	39.0	70.5	Υ		

Community Name	CID	Total Community Population ¹	Percent of Population in Project Area ²	Total Community Land Area (sq mi) ³	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Prospect	090151	8,707	0	14.3	0.1	Υ		
Town of Woodbridge	090153	8,983	48.5	18.8	43.5	Υ		

¹From aggregated census block data in Hazus

Community-specific results are provided on subsequent pages. Data provided below and on subsequent pages only include areas located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals.

Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.2.2 Flood Risk Datasets

As a part of this Flood Risk Project, flood risk datasets were created for inclusion in the Flood Risk Database. Those datasets are summarized for this Flood Risk Project below:

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the Quinnipiac Watershed project study area were updated due to new engineering analysis and redelineation performed within the Flood Risk Project. The updated modeling produced new flood zone areas and new base flood elevations in some areas and leveraged recently developed LiDAR-based topographic data for the Flood Risk Project. The data in this section reflects a comparison between the effective FIRM(s) and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the watershed.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	20.4	2.7	2.5	0.2
Within Floodway	5.4	0.5	0.4	0.1

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of Quinnipiac Watershed, the figures in this table only represent information within the panel footprint of this study in the Quinnipiac Watershed.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

²Estimated by census blocks

³From aggregated census block size in Hazus

The table below summarizes the increases, decreases, and net change of affected structures and population for the watershed.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of Quinnipiac Watershed, the figures in this table only represent information within the panel footprint of this study in the Quinnipiac Watershed.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. During this Risk MAP project, FEMA confirmed several areas within this watershed as having mitigation potential and encourages the communities within the watershed to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures. Specific areas within each jurisdiction are detailed within the individual community summaries.

• Flood Depth and Analysis Grids

o The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.

• Flood Risk Results Information

O The Quinnipiac Watershed's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were estimated as well as potential loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

			Estimated Potential Losses for Flood Event Scenarios									
	Total Invent	ory	10% (10-)	/r)	2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents												
Commercial Building + Contents												
Other Building + Contents												
Total Building + Contents ³												
Business Disruption ⁴												
TOTAL ⁵												

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

 $^{^{2}}$ Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

3.3 Communities

The following sections provide an overview of the communities' floodplain management program as of the date of this publication, as well as summarize the flood risk analysis performed for each project area in Quinnipiac Watershed.

3.3.1 City of Bristol Summary (CID 090023)

The following pages include Flood Risk data for the City of Bristol.

3.3.1.1 Overview

The City of Bristol is one of the 29 communities within Hartford County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Bristol	090023	60,062	1.0	26.5	2.3	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the City of Bristol that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.1.2 Community Analyses and Results

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the City of Bristol were not updated at all in the Quinnipiac Watershed Flood Risk Project. Redelineation was performed on Quinnipiac River, which does not touch the City of Bristol, but which resulted in updates to a map panel touching the City of Bristol. All SFHAs on updated map panels were redelineated, but there were none in the City of Bristol. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	0.03	0.002	0.008	-0.006
Within Floodway	-	-	-	-

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Bristol, the figures in this table only represent information within the City of Bristol and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of New Britain, the figures in this table only represent information within the City of New Britain and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

o The City of Bristol's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were used to estimate loss ratios for multiple

scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.						

			Estimated Potential Losses for Flood Event Scenarios									
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	5,535,193,000		-	-	-	-	-	-	-	-	-	-
Commercial Building + Contents	1,669,423,000		-	ı	-	ı	-	ı	-	-	-	-
Other Building + Contents	1,136,299,000		-	-	-	-	-	-	-	-	-	-
Total Building + Contents ³	8,340,915,000	100	-	ı	-	ı	-	ı	-	-	11,478,000	0.1
Business Disruption ⁴	-		-	ı	-	ı	-	-	-	-	633,000	-
TOTAL ⁵	8,340,915,000	100	-	-	-	-	-	-	-	-	12,111,000	0.1

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the City of Bristol. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.2 City of New Britain Summary (CID 090032)

The following pages include Flood Risk data for the City of New Britain.

3.3.2.1 **Overview**

The City of New Britain is one of the 29 communities within Hartford County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of New Britain	090032	71,538	3.9	13.3	7.9	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the City of New Britain that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.2.2 Community Analyses and Results

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the City of New Britain were updated due to new engineering analysis performed on Quinnipiac River. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. The only area of increase in flood zone area is the channel of the Quinnipiac River, and there was no area of decrease. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)	
Within SFHA	0.01	0.01	0.00	0.01	
Within Floodway	-	-	-	-	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of New Britain, the figures in this table only represent information within the City of New Britain and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)	
Within SFHA	N/A	N/A	N/A	N/A	
Within Floodway	Vithin Floodway N/A		N/A	N/A	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of New Britain, the figures in this table only represent information within the City of New Britain and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

The City of New Britain's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data

to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Invento	ory	10% (10-yr) 2% (50-yr))	1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)		
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	5,922,085,000	67.8	2,000	0.0	8,000	0.0	16,000	0.0	32,000	0.0	0	0.0
Commercial Building + Contents	1,693,771,000	19.4	3,000	0.0	9,000	0.0	13,000	0.0	21,000	0.0	0	0.0
Other Building + Contents	1,113,578,000	12.8	5,000	0.0	9,000	0.0	4,000	0.0	13,000	0.0	1,000	0.0
Total Building + Contents ³	8,729,434,000	100.0	10,000	0.0	26,000	0.0	33,000	0.0	66,000	0.0	1,000	0.0
Business Disruption ⁴	-	-	0	-	0	-	0	-	0	-	-	-
TOTAL ⁵	8,729,434,000	100.0	10,000	0.0	26,000	0.0	33,000	0.0	66,000	0.0	1,000	0.0

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- o Many areas of mitigation interest were identified for the City of New Britain. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.3 Town of Plainville Summary (CID 090034)

The following pages include Flood Risk data for the Town of Plainville.

3.3.3.1 Overview

The Town of Plainville is one of the 29 communities within Hartford County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Plainville	090034	17,328	68.8	9.8	67.2	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Plainville that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.3.2 Community Analyses and Results

• Changes Since Last FIRM

o Special Flood Hazard Area (SFHA) boundaries within the Town of Plainville were updated due to new engineering analysis and redelineation performed on Quinnipiac River. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Quinnipiac River (especially above Hamlin Pond, where the entire SFHA is new) and Pequabuck River (especially the eastern overbank), and areas with the greatest decrease are located also along Pequabuck River (especially the western overbank). The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)	
Within SFHA	0.83	0.11	0.15	-0.04	
Within Floodway	Within Floodway 0.30		0.01	0.02	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Plainville, the figures in this table only represent information within the Town of Plainville and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi²)	Net Change (mi ²)	
Within SFHA	N/A	N/A	N/A	N/A	
Within Floodway	Within Floodway N/A		N/A	N/A	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Plainville, the figures in this table only represent information within the Town of Plainville and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

The Town of Plainville's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to

estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios									
	Total Inventory		10% (10-yr) 2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)				
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	
Residential Building + Contents	1,742,983,000	60.0	6,698,000	0.4	16,476,000	0.9	17,831,000	1.0	27,093,000	1.6	1,195,000	0.1	
Commercial Building + Contents	667,333,000	23.0	7,711,000	1.2	17,148,000	2.6	18,151,000	2.7	24,231,000	3.6	1,287,000	0.2	
Other Building + Contents	492,441,000	17.0	5,091,000	1.0	13,782,000	2.8	8,056,000	1.6	19,405,000	3.9	1,004,000	0.2	
Total Building + Contents ³	2,902,757,000	100.0	19,500,000	0.7	47,406,000	1.6	44,038,000	1.5	70,729,000	2.4	3,486,000	0.1	
Business Disruption ⁴	-	-	695,000	-	1,978,000	-	1,965,000	-	2,646,000	-	136,000	_	
TOTAL ⁵	2,902,757,000	100.0	20,195,000	0.7	49,384,000	1.7	46,003,000	1.6	73,375,000	2.5	3,622,000	0.1	

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the Town of Plainville. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.4 Town of Southington Summary (CID 090037)

The following pages include Flood Risk data for the Town of Southington.

3.3.4.1 Overview

The Town of Southington is one of the 29 communities within Hartford County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Southington	090037	39,728	78.4	36.0	58.2	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Southington that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.4.2 Community Analyses and Results

• Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the Town of Southington were updated due to redelineation performed on Quinnipiac River. The redelineation modified the flood zone areas (but not base flood elevations) and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Small areas of increase in flood zone area are located along Quinnipiac River, Patton Brook, Misery Brook, Spring Lake Brook, and Eightmile River, and similar areas of decrease are located along the same reaches. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)	
Within SFHA	1.55	0.20	0.30	-0.10	
Within Floodway	Within Floodway 0.56		0.02	0.00	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Southington, the figures in this table only represent information within the Town of Southington and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Southington, the figures in this table only represent information within the Town of Southington and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

 The Town of Southington's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimated	d Poter	ntial Losses for	Flood	Event Scenario	S		
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	3,993,447,000	66.1	7,565,000	0.2	21,362,000	0.5	25,184,000	0.6	32,914,000	0.8	1,550,000	0.0
Commercial Building + Contents	1,276,289,000	21.1	18,160,000	1.4	32,918,000	2.6	38,036,000	3.0	48,143,000	3.8	2,685,000	0.2
Other Building + Contents	767,321,000	12.7	6,314,000	0.8	11,684,000	1.5	0	0.0	17,429,000	2.3	945,000	0.1
Total Building + Contents ³	6,037,057,000	100.0	32,039,000	0.5	65,964,000	1.1	62,879,000	1.0	98,486,000	1.6	5,180,000	0.1
Business Disruption ⁴	-	-	1,308,000	-	2,358,000	-	2,286,000	-	3,413,000	-	169,000	-
TOTAL ⁵	6,037,057,000	100.0	33,347,000	0.6	68,322,000	1.1	65,165,000	1.1	101,899,000	1.7	5,349,000	0.1

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

	Number of	
Type of Mitigation Interest	Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- o Many areas of mitigation interest were identified for the Town of Southington. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.5 City of Ansonia Summary (CID 090071)

The following pages include Flood Risk data for the City of Ansonia.

3.3.5.1 *Overview*

The City of Ansonia is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Ansonia	090071	18,554	17.9	6.0	23.9	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the City of Ansonia that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.5.2 Community Analyses and Results

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the City of Ansonia were updated due to new engineering analysis performed on Wepawaug River. Wepawaug River does not touch the community, but a map panel touching the river was updated, and all SFHAs on the map panel were redelineated. The redelineation modified the flood zone areas (but not base flood elevations) and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Two Mile Brook, and areas with the greatest decrease are located around Parkers Pond. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	Within SFHA 0.13		0.01	0.01
Within Floodway	0.06	0.00	0.00	0.00

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Ansonia, the figures in this table only represent information within the City of Ansonia and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Ansonia, the figures in this table only represent information within the City of Ansonia and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

o The City of Ansonia's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to

estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimate	d Potei	ntial Losses for	Flood	Event Scenarios			
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	1,641,393,000	61.9	1,545,000	0.1	1,986,000	0.1	2,150,000	0.1	2,605,000	0.2	181,000	0.0
Commercial Building + Contents	355,454,000	13.4	310,000	0.1	368,000	0.1	388,000	0.1	437,000	0.1	31,000	0.0
Other Building + Contents	655,612,000	24.7	61,000	0.0	76,000	0.0	0	0.0	98,000	0.0	3,000	0.0
Total Building + Contents ³	2,652,459,000	100.0	1,916,000	0.1	2,430,000	0.1	2,180,000	0.1	3,140,000	0.1	215,000	0.0
Business Disruption⁴	-	-	12,000	-	15,000	-	15,000	-	22,000	-	1,000	-
TOTAL ⁵	2,652,459,000	100.0	1,928,000	0.1	2,445,000	0.1	2,195,000	0.1	3,162,000	0.1	216,000	0.0

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the City of Ansonia. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.6 Town of Branford Summary (CID 090073)

The following pages include Flood Risk data for the Town of Branford.

3.3.6.1 Overview

The Town of Branford is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Branford	090073	28,683	34.7	22.0	43.9	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Branford that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.6.2 Community Analyses and Results

• Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the Town of Branford were updated due to new engineering analysis performed on Branford River and Farm River. Farm River does not touch the community, but a map panel touching the river was updated, and all SFHAs on the map panel were redelineated. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area and greatest decrease are located along Branford River and Pisgah Brook. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	Within SFHA 1.68		0.09	-0.03
Within Floodway	0.10	0.02	0.03	-0.01

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Branford, the figures in this table only represent information within the Town of Branford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi²)	Net Change (mi²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Branford, the figures in this table only represent information within the Town of Branford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - > Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

The Town of Branford's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to

estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimate	d Potei	ntial Losses for	Flood	Event Scenario	S		
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	3,197,975,000	63.6	902,000	0.0	1,973,000	0.1	2,474,000	0.1	3,307,000	0.1	148,000	0.0
Commercial Building + Contents	1,204,424,000	24.0	8,935,000	0.7	12,698,000	1.1	14,536,000	1.2	18,291,000	1.5	1,135,000	0.1
Other Building + Contents	626,069,000	12.5	5,975,000	1.0	8,316,000	1.3	6,291,000	1.0	11,457,000	1.8	741,000	0.1
Total Building + Contents ³	5,028,468,000	100.0	15,812,000	0.3	22,987,000	0.5	23,301,000	0.5	33,055,000	0.7	2,024,000	0.0
Business Disruption ⁴	-	-	905,000	-	1,280,000	-	1,325,000	-	1,770,000	-	107,000	-
TOTAL ⁵	5,028,468,000	100.0	16,717,000	0.3	24,267,000	0.5	24,626,000	0.5	34,825,000	0.7	2,131,000	0.0

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the Town of Branford. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.7 Town of Cheshire Summary (CID 090074)

The following pages include Flood Risk data for the Town of Cheshire.

3.3.7.1 Overview

The Town of Cheshire is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Cheshire	090074	28,543	65.9	32.9	62.3	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Cheshire that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.7.2 Community Analyses and Results

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the Town of Cheshire were updated due to new engineering analysis performed on Mill River and redelineation performed on Quinnipiac River. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. The redelineation modified the flood zone areas but not the base flood elevations. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Quinnipiac River, Honeypot Brook, and Willow Brook No.1 and its tributaries, and areas with the greatest decrease are located along Mill River and Tenmile River. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)	
Within SFHA	Within SFHA 1.90		0.39	-0.20	
Within Floodway	Within Floodway 0.42		0.05	-0.03	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Cheshire, the figures in this table only represent information within the Town of Cheshire and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)		
Within SFHA	N/A	N/A	N/A	N/A		
Within Floodway	in Floodway N/A		N/A	N/A		

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Cheshire, the figures in this table only represent information within the Town of Cheshire and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

The Town of Cheshire's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to

estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	2,903,217,000	62.4	4,780,000	0.2	8,409,000	0.3	10,064,000	0.3	14,204,000	0.5	708,000	0.0
Commercial Building + Contents	1,137,001,000	24.4	5,517,000	0.5	8,441,000	0.7	9,909,000	0.9	15,461,000	1.4	734,000	0.1
Other Building + Contents	615,993,000	13.2	5,324,000	0.9	7,548,000	1.2	0	0.0	11,906,000	1.9	664,000	0.1
Total Building + Contents ³	4,656,211,000	100.0	15,621,000	0.3	24,398,000	0.5	19,228,000	0.4	41,571,000	0.9	2,106,000	0.0
Business Disruption ⁴	-	-	790,000	-	1,122,000	-	944,000	-	1,862,000	-	92,000	-
TOTAL ⁵	4,656,211,000	100.0	16,411,000	0.4	25,520,000	0.5	20,172,000	0.4	43,433,000	0.9	2,198,000	0.0

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the Town of Cheshire. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.8 City of Derby Summary (CID 090075)

The following pages include Flood Risk data for the City of Derby.

3.3.8.1 Overview

The City of Derby is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Derby	090075	12,391	21.0	5.0	21.2	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the City of Derby that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.8.2 Community Analyses and Results

• Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the City of Derby were updated due to new engineering analysis performed on Wepawaug River. Wepawaug River does not touch the community, but a map panel touching the river was updated, and all SFHAs on the map panel were redelineated. The redelineation modified the flood zone areas (but not base flood elevations) and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area and areas the greatest decrease are located along Two Mile Brook. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)	
Within SFHA	0.09	0.02	0.02	0.00	
Within Floodway	-	-	-	-	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Derby, the figures in this table only represent information within the City of Derby and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)		
Within SFHA	N/A	N/A	N/A	N/A		
Within Floodway	in Floodway N/A		N/A	N/A		

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Derby, the figures in this table only represent information within the City of Derby and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

o The City of Derby's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to

estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	1,195,661,000	66.1	-	-	-	-	-	-	-	-	-	-
Commercial Building + Contents	399,603,000	22.1	-	,	-	-	-	-	-	-	-	-
Other Building + Contents	214,372,000	11.8	-	-	·	-	-	-	-	-	-	-
Total Building + Contents ³	1,809,636,000	100.0	-	1	-	-	-	-	-	-	-	-
Business Disruption ⁴	-	-	ı	-	-	-	-	-	-	-	-	-
TOTAL ⁵	1,809,636,000	100.0	-	-	-	-	-	-	-	-	-	-

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the City of Derby. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.9 Town of East Haven Summary (CID 090076)

The following pages include Flood Risk data for the Town of East Haven.

3.3.9.1 Overview

The Town of East Haven is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of East Haven	090076	28,189	72.5	12.3	76.1	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of East Haven that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.9.2 Community Analyses and Results

Changes Since Last FIRM

o Special Flood Hazard Area (SFHA) boundaries within the Town of East Haven were updated due to new engineering analysis performed on Farm River. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area and the greatest decrease are located along Farm River and its Tributary D. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	Within SFHA 1.50		0.28	-0.18
Within Floodway	0.18	0.01	0.12	-0.11

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of East Haven, the figures in this table only represent information within the Town of East Haven and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of East Haven, the figures in this table only represent information within the Town of East Haven and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

The Town of East Haven's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data

to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimate	d Potei	ntial Losses for	Flood I	Event Scenarios			
	Total Inventor	ry	10% (10-yr)		2% (50-yr)	2% (50-yr)		1% (100-yr)			Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	2,590,291,000	71.8	4,627,000	0.2	11,018,000	0.4	15,720,000	0.6	23,701,000	0.9	871,000	0.0
Commercial Building + Contents	646,926,000	17.9	2,772,000	0.4	5,050,000	0.8	6,687,000	1.0	9,110,000	1.4	423,000	0.1
Other Building + Contents	369,588,000	10.2	1,305,000	0.4	2,650,000	0.7	0	0.0	5,625,000	1.5	224,000	0.1
Total Building + Contents ³	3,606,805,000	100.0	8,704,000	0.2	18,718,000	0.5	18,367,000	0.5	38,436,000	1.1	1,518,000	0.0
Business Disruption ⁴	-	-	179,000	-	337,000	-	332,000	-	645,000	-	24,000	-
TOTAL ⁵	3,606,805,000	100.0	8,883,000	0.2	19,055,000	0.5	18,699,000	0.5	39,081,000	1.1	1,542,000	0.0

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- o Many areas of mitigation interest were identified for the Town of East Haven. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.10 Town of Guilford Summary (CID 090077)

The following pages include Flood Risk data for the Town of Guilford.

3.3.10.1 *Overview*

The Town of Guilford is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Guilford	090077	21,398	0.1	47.1	1.5	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Guilford that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.10.2 Community Analyses and Results

Changes Since Last FIRM

O Special Flood Hazard Area (SFHA) boundaries within the Town of Guilford were not updated at all in the Quinnipiac Watershed Flood Risk Project. New engineering analysis was performed on Farm River, which does not touch the Town of Guilford, but which resulted in updates to a map panel touching the Town of Guilford. All SFHAs on updated map panels were redelineated, but there were none in the Town of Guilford. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	-	-	-	-
Within Floodway	-	-	-	-

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Guilford, the figures in this table only represent information within the Town of Guilford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of New Britain, the figures in this table only represent information within the City of New Britain and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further
 isolate these and other areas where flood mitigation potential is high. The FRD includes data
 which may be helpful in planning and implementing mitigation strategies. Properties located
 in areas expected to experience some depth of water should seriously consider mitigation
 options for implementation.

• Areas of Mitigation Interest

No Areas of Mitigation Interest were identified for the Town of Guilford in the Quinnipiac
 Watershed Flood Risk Project area.

• Hazus Estimated Loss Information

O The Town of Guilford's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimate	d Potei	ntial Losses for	Flood	Event Scenario	S		
	Total Inventory		10% (10-yr)		2% (50-yr)	2% (50-yr)		1% (100-yr)		r)	Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	2,600,164,000	69.2	-	-	-	-	-	-	-	-	-	-
Commercial Building + Contents	727,597,000	19.4	-	-	-	-	-	-	-	-	-	-
Other Building + Contents	430,098,000	11.4	-		-	-	-	-	-	-	-	-
Total Building + Contents ³	3,757,859,000	100.0	-	,	-	-	-	-	,	-	-	-
Business Disruption ⁴	-	-	-	-	-	-	-	-	-	-	-	-
TOTAL ⁵	3,757,859,000	100.0	-	-	-	-	-	-	-	-	-	-

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

3.3.11 Town of Hamden Summary (CID 090078)

The following pages include Flood Risk data for the Town of Hamden.

3.3.11.1 Overview

The Town of Hamden is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Hamden	090078	56,913	74.2	32.8	67.9	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Hamden that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.11.2 Community Analyses and Results

Changes Since Last FIRM

o Special Flood Hazard Area (SFHA) boundaries within the Town of Hamden were updated due to new engineering analysis performed on Mill River and redelineation performed on Quinnipiac River. Quinnipiac River does not touch the community, but a map panel touching the river was updated, and all SFHAs on the map panel were redelineated. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. The redelineation modified the flood zone areas but not the base flood elevations. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Mill River, Butterworth Brook, Eaton Brook, and Jepp Brook, and areas with the greatest decrease are located along Mill River and some small Zones A representing ponding. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)		
Within SFHA	2.49	0.35	0.30	0.05		
Within Floodway	0.75	0.16	0.03	0.13		

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Hamden, the figures in this table only represent information within the Town of Hamden and the Quinnipiac Watershed project study area.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi²)	Net Change (mi ²)	
Within SFHA	N/A	N/A	N/A	N/A	
Within Floodway	N/A	N/A	N/A	N/A	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Hamden, the figures in this table only represent information within the Town of Hamden and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Hazus Estimated Loss Information

O The Town of Hamden's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimated	d Potei	ntial Losses for	Flood	Event Scenario	S		
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	5,753,517,000	70.1	12,494,000	0.2	27,972,000	0.5	36,102,000	0.6	51,667,000	0.9	2,191,000	0.0
Commercial Building + Contents	1,571,576,000	19.2	17,227,000	1.1	27,296,000	1.7	31,773,000	2.0	41,610,000	2.6	2,349,000	0.1
Other Building + Contents	880,775,000	10.7	5,412,000	0.6	8,745,000	1.0	0	0.0	13,927,000	1.6	746,000	0.1
Total Building + Contents ³	8,205,868,000	100.0	35,133,000	0.4	64,013,000	0.8	60,634,000	0.7	107,204,000	1.3	5,286,000	0.1
Business Disruption⁴	-	-	662,000	-	1,125,000	-	1,147,000	-	1,865,000	-	75,000	-
TOTAL ⁵	8,205,868,000	100.0	35,795,000	0.4	65,138,000	0.8	61,781,000	0.8	109,069,000	1.3	5,361,000	0.1

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

	Number of	
Type of Mitigation Interest	Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the Town of Hamden. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.12 City of Meriden Summary (CID 090081)

The following pages include Flood Risk data for the City of Meriden.

3.3.12.1 *Overview*

The City of Meriden is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Meriden	090081	58,244	34.5	23.7	46.7	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the City of Meriden that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.12.2 Community Analyses and Results

Changes Since Last FIRM

o Special Flood Hazard Area (SFHA) boundaries within the City of Meriden were updated due to new engineering analysis performed on Spoon Shop Brook and redelineation performed on Muddy River and Quinnipiac River. Muddy River does not touch the community, but a map panel touching the river was updated, and all SFHAs on the map panel were redelineated. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. The redelineation modified the flood zone areas but not the base flood elevations. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Spoon Shop Brook (especially the upper reach, which hadn't been mapped before), and areas with the greatest decrease are located also along Spoon Shop Brook, its Zone A tributaries, and Willow Brook No. 2. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	0.97	0.10	0.17	-0.07
Within Floodway	0.23	0.02	0.01	0.01

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Meriden, the figures in this table only represent information within the City of Meriden and the Quinnipiac Watershed project study area.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	tal Area (mi²) Increase (mi²)		Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Meriden, the figures in this table only represent information within the City of Meriden and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further
 isolate these and other areas where flood mitigation potential is high. The FRD includes data
 which may be helpful in planning and implementing mitigation strategies. Properties located
 in areas expected to experience some depth of water should seriously consider mitigation
 options for implementation.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Hazus Estimated Loss Information

O The City of Meriden's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	5,338,035,000	66.2	332,000	0.0	791,000	0.0	7,458,000	0.1	1,120,000	0.0	104,000	0.0
Commercial Building + Contents	1,480,542,000	18.4	243,000	0.0	434,000	0.0	2,116,000	0.1	581,000	0.0	39,000	0.0
Other Building + Contents	1,242,994,000	15.4	118,000	0.0	234,000	0.0	0	0.0	326,000	0.0	23,000	0.0
Total Building + Contents ³	8,061,571,000	100.0	693,000	0.0	1,459,000	0.0	9,406,000	0.1	2,027,000	0.0	166,000	0.0
Business Disruption ⁴	-	-	2,000	-	10,000	-	173,000	-	13,000	-	1,000	-
TOTAL ⁵	8,061,571,000	100.0	695,000	0.0	1,469,000	0.0	9,579,000	0.1	2,040,000	0.0	167,000	0.0

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the City of Meriden. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.13 City of Milford Summary (CID 090082)

The following pages include Flood Risk data for the City of Milford.

3.3.13.1 *Overview*

The City of Milford is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Milford	090082	52,305	26.6	22.6	42.1	Y		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the City of Milford that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.13.2 Community Analyses and Results

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the City of Milford were updated due to redelineation performed on Wepawaug River. The redelineation modified the flood zone areas (but not base flood elevations) and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Wepawaug River and Stubby Brook, and there are not many areas of decrease. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	1.51	0.13	0.04	0.09
Within Floodway	0.36	0.00	0.00	0.00

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Milford, the figures in this table only represent information within the City of Milford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)		
Within SFHA	N/A	N/A	N/A	N/A		
Within Floodway	N/A	N/A	N/A	N/A		

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of Milford, the figures in this table only represent information within the City of Milford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

 The City of Milford's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Inventor	ry	10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr		Annualized (\$/	yr)
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	5,541,274,000	61.1	6,280,000	0.1	13,325,000	0.2	17,159,000	0.3	30,191,000	0.5	1,078,000	0.0
Commercial Building + Contents	2,325,758,000	25.6	8,577,000	0.4	13,395,000	0.6	17,261,000	0.7	26,064,000	1.1	1,197,000	0.1
Other Building + Contents	1,201,534,000	13.2	1,550,000	0.1	3,040,000	0.3	0	0.0	7,122,000	0.6	242,000	0.0
Total Building + Contents ³	9,068,566,000	100.0	16,407,000	0.2	29,760,000	0.3	28,489,000	0.3	63,377,000	0.7	2,517,000	0.0
Business Disruption⁴	-	-	189,000	-	373,000	-	410,000	-	1,037,000	-	17,000	-
TOTAL ⁵	9,068,566,000	100.0	16,596,000	0.2	30,133,000	0.3	28,899,000	0.3	64,414,000	0.7	2,534,000	0.0

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the City of Milford. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.14 City of New Haven Summary (CID 090084)

The following pages include Flood Risk data for the City of New Haven.

3.3.14.1 *Overview*

The City of New Haven is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of New Haven	090084	123,626	23.0	18.8	17.0	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the City of New Haven that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.14.2 Community Analyses and Results

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the City of New Haven were not updated at all in the Quinnipiac Watershed Flood Risk Project. New engineering analysis on Farm River and redelineation on Quinnipiac River were performed, which do not touch the City of New Haven, but which resulted in updates to map panels touching the City of New Haven. All riverine SFHAs on updated map panels were redelineated, but there were none in the City of New Haven. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	0.08	0.00	0.00	0.00
Within Floodway	-	-	-	-

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of New Haven, the figures in this table only represent information within the City of New Haven and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of New Britain, the figures in this table only represent information within the City of New Britain and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

Areas of Mitigation Interest

No Areas of Mitigation Interest were identified for the City of New Haven in the Quinnipiac
 Watershed Flood Risk Project area.

• Hazus Estimated Loss Information

O The City of New Haven's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimate	d Pote	ntial Losses for	Flood	Event Scenaric	S		
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	10,188,590,000	40.9	-	-	-	-	-	-	-	-	-	-
Commercial Building + Contents	8,670,294,000	34.8	-	-	-	-	-	-	-	-	-	-
Other Building + Contents	6,036,753,000	24.2	-	-	-	-	-	-	-	-	-	_
Total Building + Contents ³	24,895,637,000	100.0	-	-	-	1	-	1	-	-	-	-
Business Disruption ⁴	=	-	-	-	-	-	-	-	-	-	-	_
TOTAL ⁵	24,895,637,000	100.0	-	-	-	-	-	-	-	-	-	-

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

3.3.15 Town of North Branford Summary (CID 090085)

The following pages include Flood Risk data for the Town of North Branford.

3.3.15.1 Overview

The Town of North Branford is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of North Branford	090085	13,906	89.2	24.9	82.4	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of North Branford that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.15.2 Community Analyses and Results

Changes Since Last FIRM

O Special Flood Hazard Area (SFHA) boundaries within the Town of North Branford were updated due to new engineering analysis performed on Branford River, Farm River, and Muddy River. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Branford River and its tributaries and Muddy River and its tributaries (especially the reaches that hadn't been mapped before), and areas with the greatest decrease are located along Farm River. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	1.56	0.43	0.26	0.17
Within Floodway	0.31	0.10	0.10	0.00

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of North Branford, the figures in this table only represent information within the Town of North Branford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi²)	Net Change (mi²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of North Branford, the figures in this table only represent information within the Town of North Branford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

Hazus Estimated Loss Information

 The Town of North Branford's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimated	d Poter	ntial Losses for	Flood I	Event Scenarios			
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	1,399,794,000	72.1	8,404,000	0.6	11,928,000	0.9	14,200,000	1.0	18,400,000	1.3	1,050,000	0.1
Commercial Building + Contents	282,961,000	14.6	9,947,000	3.5	12,766,000	4.5	13,977,000	4.9	15,644,000	5.5	1,149,000	0.4
Other Building + Contents	259,519,000	13.4	7,584,000	2.9	10,471,000	4.0	0	0.0	13,859,000	5.3	922,000	0.4
Total Building + Contents ³	1,942,274,000	100.0	25,935,000	1.3	35,165,000	1.8	27,526,000	1.4	47,903,000	2.5	3,121,000	0.2
Business Disruption ⁴	-	-	785,000	-	1,037,000	-	794,000	-	1,331,000	-	74,000	_
TOTAL ⁵	1,942,274,000	100.0	26,720,000	1.4	36,202,000	1.9	28,320,000	1.5	49,234,000	2.5	3,195,000	0.2

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the Town of North Branford. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.16 Town of North Haven Summary (CID 090086)

The following pages include Flood Risk data for the Town of North Haven.

3.3.16.1 *Overview*

The Town of North Haven is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of North Haven	090086	23,035	100	20.8	98.0	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of North Haven that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.16.2 Community Analyses and Results

Changes Since Last FIRM

O Special Flood Hazard Area (SFHA) boundaries within the Town of North Haven were updated due to new engineering analysis performed on Farm River, Mill River, and Muddy River and redelineation performed on Muddy River and Quinnipiac River. Farm River does not touch the community, but a map panel touching the river was updated, and all SFHAs on the map panel were redelineated. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. The redelineation modified the flood zone areas but not the base flood elevations. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Quinnipiac River, Watermans Brook, and Muddy River, and areas with the decrease are spotty. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	2.73	0.35	0.09	0.26
Within Floodway	0.85	0.03	0.01	0.02

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of North Haven, the figures in this table only represent information within the Town of North Haven and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of North Haven, the figures in this table only represent information within the Town of North Haven and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

The Town of North Haven's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

					Estimated	d Poter	ntial Losses for	Flood	Event Scenario	S		
	Total Inventor	ry	10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²								
Residential Building + Contents	2,520,682,000	56.9	5,410,000	0.2	10,705,000	0.4	13,784,000	0.5	22,736,000	0.9	900,000	0.0
Commercial Building + Contents	1,207,597,000	27.2	21,151,000	1.8	28,878,000	2.4	32,864,000	2.7	45,461,000	3.8	2,633,000	0.2
Other Building + Contents	704,261,000	15.9	36,159,000	5.1	49,513,000	7.0	45,341,000	6.4	76,140,000	10.8	4,541,000	0.6
Total Building + Contents ³	4,432,540,000	100.0	62,720,000	1.4	89,096,000	2.0	91,989,000	2.1	144,337,000	3.3	8,074,000	0.2
Business Disruption ⁴	-	-	4,994,000	-	6,660,000	-	6,889,000	_	9,891,000	-	601,000	-
TOTAL ⁵	4,432,540,000	100.0	67,714,000	1.5	95,756,000	2.2	98,878,000	2.2	154,228,000	3.5	8,675,000	0.2

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

	Number of	
Type of Mitigation Interest	Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- o Many areas of mitigation interest were identified for the Town of North Haven. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.17 Town of Orange Summary (CID 090087)

The following pages include Flood Risk data for the Town of Orange.

3.3.17.1 *Overview*

The Town of Orange is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Orange	090087	13,233	58.7	17.2	59.6	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Orange that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.17.2 Community Analyses and Results

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the Town of Orange were updated due to new engineering analysis and redelineation performed on Wepawaug River. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. The redelineation modified the flood zone areas but not the base flood elevations. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Wepawaug River (especially the reach that hadn't been mapped before), and areas with decrease are spotty. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	0.57	0.20	0.02	0.18
Within Floodway	0.21	0.03	0.00	0.03

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Orange, the figures in this table only represent information within the Town of Orange and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Orange, the figures in this table only represent information within the Town of Orange and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

• Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

 The Town of Orange's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Inventor	ry	10% (10-yr)	10% (10-yr)		2% (50-yr)		1% (100-yr)			Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	1,511,527,000	56.7	2,973,000	0.2	5,382,000	0.4	7,096,000	0.5	10,825,000	0.7	463,000	0.0
Commercial Building + Contents	832,354,000	31.2	2,274,000	0.3	3,468,000	0.4	4,091,000	0.5	5,193,000	0.6	302,000	0.0
Other Building + Contents	320,973,000	12.0	186,000	0.1	286,000	0.1	0	0.0	412,000	0.1	22,000	0.0
Total Building + Contents ³	2,664,854,000	100.0	5,433,000	0.2	9,136,000	0.3	10,832,000	0.4	16,430,000	0.6	787,000	0.0
Business Disruption⁴	-	-	45,000	-	71,000	-	87,000	-	113,000	-	5,000	-
TOTAL ⁵	2,664,854,000	100.0	5,478,000	0.2	9,207,000	0.3	10,919,000	0.4	16,543,000	0.6	792,000	0.0

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the Town of Orange. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- o Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14
 mitigation projects for this area, and to date only 2 have been implemented. During this Risk
 MAP project, FEMA confirmed that this area has mitigation potential and encouraged the
 community to continue working with the State Hazard Mitigation Officer to further identify
 and mitigate these high-risk areas and structures.

3.3.18 Town of Wallingford Summary (CID 090090)

The following pages include Flood Risk data for the Town of Wallingford.

3.3.18.1 *Overview*

The Town of Wallingford is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Wallingford	090090	43,026	74.5	39.0	70.5	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Wallingford that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.18.2 Community Analyses and Results

• Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the Town of Wallingford were updated due to new engineering analysis performed on Farm River and Muddy River and redelineation performed on Muddy River and Quinnipiac River. Farm River does not touch the community, but a map panel touching the river was updated, and all SFHAs on the map panel were redelineated. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. The redelineation modified the flood zone areas but not the base flood elevations. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Quinnipiac River and Muddy River, and areas with the greatest decrease are located also along Quinnipiac River and Wharton Brook. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	2.23	0.23	0.37	-0.14
Within Floodway	0.90	0.02	0.02	0.00

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Wallingford, the figures in this table only represent information within the Town of Wallingford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi²)	Net Change (mi ²)	
Within SFHA	N/A	N/A	N/A	N/A	
Within Floodway	ithin Floodway N/A		N/A	N/A	

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Wallingford, the figures in this table only represent information within the Town of Wallingford and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

• Hazus Estimated Loss Information

O The Town of Wallingford's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Inventor	ry	10% (10-yr)	2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/		yr)
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	4,153,114,000	56.2	5,943,000	0.1	11,837,000	0.3	15,463,000	0.4	20,358,000	0.5	958,000	0.0
Commercial Building + Contents	1,796,741,000	24.3	18,297,000	1.0	27,037,000	1.5	31,326,000	1.7	36,645,000	2.0	2,364,000	0.1
Other Building + Contents	1,442,036,000	19.5	21,894,000	1.5	34,399,000	2.4	14,647,000	1.0	47,913,000	3.3	2,978,000	0.2
Total Building + Contents ³	7,391,891,000	100.0	46,134,000	0.6	73,273,000	1.0	61,436,000	0.8	104,916,000	1.4	6,300,000	0.1
Business Disruption⁴	-	-	2,477,000	-	3,991,000	-	3,106,000	-	5,453,000	-	330,000	_
TOTAL ⁵	7,391,891,000	100.0	48,611,000	0.7	77,264,000	1.0	64,542,000	0.9	110,369,000	1.5	6,630,000	0.1

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- Many areas of mitigation interest were identified for the City of Bristol. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14 mitigation projects for this area, and to date only 2 have been implemented. During this Risk MAP project, FEMA confirmed that this area has mitigation potential and encouraged the community to continue working with the State Hazard Mitigation Officer to further identify and mitigate these high-risk areas and structures.

3.3.19 Town of Prospect Summary (CID 090151)

The following pages include Flood Risk data for the Town of Prospect.

3.3.19.1 *Overview*

The Town of Prospect is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Prospect	090151	8,707	0	14.3	0.1	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Prospect that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.19.2 Community Analyses and Results

Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the Town of Prospect were not updated at all in the Quinnipiac Watershed Flood Risk Project. New engineering analysis was performed on Mill River, which does not touch the Town of Prospect, but which resulted in updates to a map panel touching the Town of Prospect. All SFHAs on updated map panels were redelineated, but there were none in the Town of Prospect. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	-	-	-	-
Within Floodway	-	-	-	-

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Prospect, the figures in this table only represent information within the Town of Prospect and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi²)	Net Change (mi²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the City of New Britain, the figures in this table only represent information within the City of New Britain and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - > Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further
 isolate these and other areas where flood mitigation potential is high. The FRD includes data
 which may be helpful in planning and implementing mitigation strategies. Properties located
 in areas expected to experience some depth of water should seriously consider mitigation
 options for implementation.

Areas of Mitigation Interest

 No Areas of Mitigation Interest were identified for the Town of Prospect in the Quinnipiac Watershed Flood Risk Project area.

Hazus Estimated Loss Information

O The Town of Prospect's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Inventor	ry	10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/	yr)
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	889,554,000	71.7	-	-	-	-	-	-	-	-	-	-
Commercial Building + Contents	188,091,000	15.2	-	-	-	-	-	-	-	-	-	-
Other Building + Contents	162,171,000	13.1	-	-	-	-	-		-	-	-	-
Total Building + Contents ³	1,239,816,000	100.0	-	,	-	-	-	,	-		-	-
Business Disruption ⁴	-	-	-	-	-	-	-	1	-	-	-	-
TOTAL ⁵	1,239,816,000	100.0	-	-	-	-	-	-	-	-	-	-

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

3.3.20 Town of Woodbridge Summary (CID 090153)

The following pages include Flood Risk data for the Town of Woodbridge.

3.3.20.1 Overview

The Town of Woodbridge is one of the 28 communities within New Haven County. The information below provides an overview of the community's floodplain management program information as of the date of this publication.

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Town of Woodbridge	090153	8,983	48.5	18.8	43.5	Υ		

- Participating in the County A Multi-Hazard Mitigation Plan which expires [Insert Date]
- Past Federal Disaster Declarations for flooding = [Insert Number]
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = [Insert Number] policies totaling approximately [Insert Dollar Amount]
- NFIP-recognized repetitive loss properties = [Insert Number] [(Insert Property Types)]
- NFIP-recognized severe repetitive loss properties = [Insert Number] [(Insert Property Types)]

Data provided below only includes areas within the Town of Woodbridge that are located within the Quinnipiac Watershed Flood Risk Project and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.20.2 Community Analyses and Results

• Changes Since Last FIRM

Special Flood Hazard Area (SFHA) boundaries within the Town of Woodbridge were updated due to new engineering analysis and redelineation performed on Wepawaug River. The updated modeling produced new flood zone areas and new base flood elevations and leveraged the region's recently developed LiDAR-based topographic data. The redelineation modified the flood zone areas but not the base flood elevations. Also, population and building data were provided by the community, which were used to analyze changes in numbers of persons and buildings in areas of change. Areas with the greatest increase in flood zone area are located along Wepawaug River and Race Brook, and areas with the greatest decrease are spotty. The data in this section reflects the comparison between the effective FIRM and the new analysis in this study.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA	0.50	0.19	0.04	0.15
Within Floodway	0.15	0.03	0.00	0.03

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Woodbridge, the figures in this table only represent information within the Town of Woodbridge and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

The table below summarizes the increases, decreases, and net change of affected structures and population for the community.

Area of Study	Total Area (mi²)	Increase (mi²)	Decrease (mi ²)	Net Change (mi²)
Within SFHA	N/A	N/A	N/A	N/A
Within Floodway	N/A	N/A	N/A	N/A

^{*}Although the Flood Risk Database may contain Changes Since Last FIRM information outside of the Town of Woodbridge, the figures in this table only represent information within the Town of Woodbridge and the Quinnipiac Watershed project study area.

Section 2 of the FRR provides more information regarding the source and methodology used to develop this table.

Flood Depth and Analysis Grids

- See the FRD for the following depth and analysis grid data (Section 2 of the FRR provides general information regarding the development of and potential uses for this data):
 - ➤ Multi-frequency flood depth grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Percent annual chance of flooding grids
 - Percent chance of flooding over a 30-year period grids
 - ➤ Water surface elevation grids (10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events)
 - Water surface elevation change grids
- Additional information and data layers provided within the FRD should be used to further isolate these and other areas where flood mitigation potential is high. The FRD includes data which may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation.

Hazus Estimated Loss Information

The Town of Woodbridge's flood risk analysis uses results from a FEMA-performed Hazus analysis which accounts for newly modeled areas in the Flood Risk Project and newly modeled

depths for certain flood events. Potential losses were compared with locally provided tax data to estimate loss ratios for multiple scenarios. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

				Estimated Potential Losses for Flood Event Scenarios								
	Total Inventor	ry	10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-y	r)	Annualized (\$/	yr)
	Estimated Value	% of Total	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²	Dollar Losses ¹	Loss Ratio ²
Residential Building + Contents	1,247,261,000	70.4	1,406,000	0.1	2,712,000	0.2	3,811,000	0.3	6,720,000	0.5	241,000	0.0
Commercial Building + Contents	368,614,000	20.8	486,000	0.1	619,000	0.2	737,000	0.2	978,000	0.3	55,000	0.0
Other Building + Contents	156,329,000	8.8	147,000	0.1	191,000	0.1	0	0.0	317,000	0.2	15,000	0.0
Total Building + Contents ³	1,772,204,000	100.0	2,039,000	0.1	3,522,000	0.2	4,218,000	0.2	8,015,000	0.5	311,000	0.0
Business Disruption ⁴	-	-	11,000	-	17,000	-	19,000	-	30,000	-	0	_
TOTAL ⁵	1,772,204,000	100.0	2,050,000	0.1	3,539,000	0.2	4,237,000	0.2	8,045,000	0.5	311,000	0.0

Source: Hazus analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

²Loss ratio = Dollar Losses / Estimated Value. Loss Ratios are rounded to the nearest tenth percent.

³Total Building + Contents Loss = (Residential Building + Contents Loss) + (Commercial Building + Contents Loss) + (Other Building + Contents Loss).

⁴Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁵Total Loss = Total Building + Contents + Business Disruption

• Areas of Mitigation Interest

 Section 2.2.4 of the FRR provides more information regarding areas of mitigation interest, how they are defined for this analysis, and potential mitigation actions that could be considered for each type. The table below summarizes the number of areas of mitigation interest by type.

Type of Mitigation Interest	Number of Areas	Data Source
Dam		
Levee		
Stream Flow Pinch Points		
Significant Land Use Changes		
Past Claims Hot Spot		
Area of Mitigation Success		

- o Many areas of mitigation interest were identified for the Town of Woodbridge. A significant factor for the Big Vista district is pinched flow on Spartan Creek at the Parson Street Bridge. It should also be noted that the Shady Tree subdivision was previously mapped outside of the SFHA as a provisionally accredited levee zone. The levee has since been de-accredited due to freeboard limitations subjecting the neighborhood to increased flood risk and resulting in expanded flood zone mapping.
- Other areas of mitigation interest include the Pike Dam, which is a high hazard dam located downstream of the Indian River. Approximately 450 structures are located immediately below this dam that could face additional risk should the dam fail. Refer to the County A Multi-Hazard Mitigation Plan for additional information regarding this structure, its area of potential impact, and its past performance during major storm events. At an intersection between New York Canal and Indian Creek, the assumption was the gates on the canal were going to control flow to the canal capacity. The gates on the canal no longer work, allowing more water in excess of the canal's capacity to handle excess flow. Therefore, an assumption was made for the Flood Risk Project that the canal would fail and the entire flow would have to enter Indian Creek, increasing the flow by 1,500 cubic feet per second (cfs) and expanding the floodplain.
- Evidence of actual flood losses can be one of the most compelling factors for increasing a community's flood risk awareness. One indicator is claims through the NFIP. While most of the city's flood claims (240 out of 268) have originated from the Big Vista district, the Highway 42 corridor is home to several others including three repetitive loss properties and one severe repetitive loss property. Most of the claims are located near the confluence of the Indian River and Spartan Creek, producing over \$18 million in claims within the last 10 years.
- According to the City of Bristol Multi-Hazard Mitigation Plan, the city has identified 14
 mitigation projects for this area, and to date only 2 have been implemented. During this Risk
 MAP project, FEMA confirmed that this area has mitigation potential and encouraged the
 community to continue working with the State Hazard Mitigation Officer to further identify
 and mitigate these high-risk areas and structures.

4 Actions to Reduce Flood Risk

In order to fully leverage the Flood Risk datasets and products created for this Flood Risk Project, local stakeholders should consider many different flood risk mitigation tactics, including, but not limited to, the items shown in the sub-sections below.

4.1 Types of Mitigation Actions

Mitigation provides a critical foundation on which to reduce loss of life and property by avoiding or lessening the impact of hazard events. This creates safer communities and facilitates resiliency by enabling communities to return to normal function as quickly as possible after a hazard event. Once a community understands its flood risk, it is in a better position to identify potential mitigation actions that can reduce the risk to its people and property.

The mitigation plan requirements in 44 CFR Part 201 encourage communities to understand their vulnerability to hazards and take actions to minimize vulnerability and promote resilience. Flood mitigation actions generally fall into the following categories:

4.1.1 Preventative Measures

Preventative measures are intended to keep flood hazards from getting worse. They can reduce future vulnerability to flooding, especially in areas where development has not yet occurred or where capital improvements have not been substantial. Examples include:

- Comprehensive land use planning
- Zoning regulations
- Subdivision regulations
- Open space preservation
- Building codes
- Floodplain development regulations
- Stormwater management
- Purchase development rights or conservation easements
- Participation in the NFIP Community Rating System (CRS)

4.1.2 Property Protection Measures

Property protection measures protect existing buildings by modifying the building to withstand floods, or by removing buildings from hazardous locations. Examples include:

Building relocation

Before Mitigation and After Mitigation





Communities will need to prioritize projects as part of the planning process. FEMA can then help route federal mitigation dollars to fund these projects.

NFIP's CRS is a voluntary incentive program that recognizes and encourages community floodplain management activities that exceed the minimum NFIP requirements. As a result, flood insurance premium rates are discounted to reflect the reduced flood risk resulting from community actions meeting the three goals of the CRS: to reduce flood losses, to facilitate accurate insurance rating, and to promote the awareness of flood insurance.

For CRS participating communities, flood insurance premium rates are discounted in increments of 5%; i.e., a Class 1 community would receive a 45% premium discount, while a Class 9 community would receive a 5% discount. (A Class 10 is not participating in the CRS and receives no discount.)

- Acquisition and clearance
- Building elevation
- Barrier installation
- Building retrofit

4.1.3 Natural Resource Protection Activities

Natural resource protection activities reduce the impact of floods by preserving or restoring natural areas such as floodplains, wetlands, and dunes and their natural functions. Examples include:

- Wetland protection
- Habitat protection
- Erosion and sedimentation control
- Best management practices (BMP)
- Prevention of stream dumping activities (anti-litter campaigns)
- Improved forestry practices such as reforesting or selective timbering (extraction)

4.1.4 Structural Mitigation Projects

Structural mitigation projects lessen the impact of floods by modifying the environmental natural progression of the flooding event. Structural protection such as upgrading dams/levees for already existing development and critical facilities may be a realistic alternative. However, citizens should be made aware of their residual risk. Examples include:

- Reservoirs, retention, and detention basins
- Levees and floodwalls
- Channel modifications
- Channel maintenance

4.1.5 Public Education and Awareness Activities

Public education and awareness activities advise residents, business owners, potential property buyers, and visitors about floods, hazardous areas, and mitigation techniques they can use to reduce the flood risk to themselves and their property. Examples include:

- Readily available and readable updated maps
- Outreach projects
- Libraries
- Technical assistance

- Real estate disclosure
- Environmental education
- Risk information via the nightly news

4.1.6 Emergency Service Measures

Although not typically considered a mitigation technique, emergency service measures minimize the impact of flooding on people and property. These are actions commonly taken immediately prior to, during, or in response to a hazard event. Examples include:

- Hazard warning system
- Emergency response plan
- COOP and COG planning
- Critical facilities protection
- Health and safety maintenance
- Post flood recovery planning

In Section 3, specific AoMIs were identified. Table 4.1 below identifies possible mitigation actions for each AoMI to consider.

Table 4-1. Mitigation Actions for Areas of Mitigation Interest

AoMI	Possible Actions to Reduce Flood Risk
Dams	Engineering assessment Dam upgrades and strengthening Emergency Action Plan Dam removal Easement creation in impoundment and downstream inundation areas
Levees (accredited and non-accredited) and significant levee- like structures	Generally same as dams above Purchase of flood insurance for at-risk structures
Coastal Structures Jetties Groynes Seawalls Other structures	Increase coastal setbacks for construction Habitat restoration programs Wetland restoration and mitigation banking programs
Stream Flow Pinch Point Undersized culverts or bridge openings	Engineering analysis Replacement of structure pre- and post-disaster
Past Claims and IA/PA Hot Spots	Acquisition Elevation Relocation Floodproofing

For more information regarding hazard mitigation techniques, best practices, and potential grant funding sources, visit www.fema.gov or contact your local floodplain manager, emergency manager, or State Hazard Mitigation Officer.

AoMI	Possible Actions to Reduce Flood Risk
Major Land Use Changes (past 5 years or next 5 years)	Higher regulatory standard Stormwater BMPs Transfer of Development rights Compensatory storage and equal conveyance standards
Key Emergency Routes Overtopped During Frequent Flooding Events	Elevation Creation of alternate routes Design as low water crossing
Areas of Significant Riverine or Coastal Erosion	Relocation of buildings and infrastructure Regulations and planning Natural vegetation Hardening
Drainage or Stormwater- Based Flood Hazard Areas, or Areas Not Identified as Floodprone on the FIRM But Known to be Inundated	Identification of all flood hazard areas
Areas of Mitigation Success	N/A

4.2 Identifying Specific Actions for Your Community

As many mitigation actions are possible to lessen the impact of floods, how can a community decide which ones are appropriate to implement? There are many ways to identify specific actions most appropriate for a community. Some factors to consider may include the following:

- **Site characteristics.** Does the site present unique challenges (e.g., significant slopes or erosion potential)?
- **Flood characteristics.** Are the flood waters affecting the site fast or slow-moving? Is there debris associated with the flow? How deep is the flooding?
- **Social acceptance.** Will the mitigation action be acceptable to the public? Does it cause social or cultural problems?
- **Technical feasibility.** Is the mitigation action technically feasible (e.g., making a building watertight to a reasonable depth)?
- Administrative feasibility. Is there administrative capability to implement the mitigation action?
- **Legal.** Does the mitigation action meet all applicable codes, regulations, and laws? Public officials may have a legal responsibility to act and inform citizens if a known hazard has been identified.

Refer to FEMA Mitigation Planning
How To Guide #3 (FEMA 386-3)
"Developing the Mitigation Plan Identifying Mitigation Actions and
Implementation Strategies" for more
information on how to identify
specific mitigation actions to
address hazard risk in your
community.

FEMA in collaboration with the American Planning Association has released the publication, "Integrating Hazard Mitigation into Local Planning." This guide explains how hazard mitigation can be incorporated into several different types of local planning programs. For more information go to www.planning.org. or http://www.fema.gov/library.

- **Economic.** Is the mitigation action affordable? Is it eligible under grant or other funding programs? Can it be completed within existing budgets?
- **Environmental.** Does the mitigation action cause adverse impacts on the environment or can they be mitigated? Is it the most appropriate action among the possible alternatives?

Your local Hazard Mitigation Plan is a valuable place to identify and prioritize possible mitigation actions. The plan includes a mitigation strategy with mitigation actions that were developed through a public and open process. You can then add to or modify those actions based on what is learned during the course of the Risk MAP project and the information provided within this FRR.

4.3 Mitigation Programs and Assistance

Not all mitigation activities require funding (e.g., local policy actions such as strengthening a flood damage prevention ordinance), and those that do are not limited to outside funding sources (e.g., inclusion in local capital improvements plan, etc.). For those mitigation actions that require assistance through funding or technical expertise, several state and federal agencies have flood hazard mitigation grant programs and offer technical assistance. These programs may be funded at different levels over time or may be activated under special circumstances such as after a presidential disaster declaration.

4.3.1 FEMA Mitigation Programs and Assistance

FEMA awards many mitigation grants each year to states and communities to undertake mitigation projects to prevent future loss of life and property resulting from hazard impacts, including flooding. The FEMA Hazard Mitigation Assistance (HMA) programs provide grants for mitigation through the programs listed in Table 4.2 below.

Table 4-2. FEMA Hazard Mitigation Assistance Programs

Mitigation Grant Program	Authorization	Purpose
Hazard Mitigation Grant Program (HMGP)	Robert T. Stafford Disaster Relief and Emergency Assistance Act	Activated after a presidential disaster declaration; provides funds on a sliding scale formula based on a percentage of the total federal assistance for a disaster for long-term mitigation measures to reduce vulnerability to natural hazards
Flood Mitigation Assistance (FMA)	National Flood Insurance Reform Act	Reduce or eliminate claims against the NFIP
Pre-Disaster Mitigation (PDM)	Disaster Mitigation Act	National competitive program focused on mitigation project and planning activities that address multiple natural hazards



Communities can link hazard mitigation plans and actions to the right FEMA grant programs to fund flood risk reduction. More information about FEMA HMA programs can be found at http://www.fema.gov/government/grant/hma/index.shtm.

Mitigation Grant Program	Authorization	Purpose
Repetitive Flood Claims (RFC)	Bunning-Bereuter- Blumenauer Flood Insurance Reform Act	Reduce flood claims against the NFIP through flood mitigation; properties must be currently NFIP insured and have had at least one NFIP claim
Severe Repetitive Loss (SRL)	Bunning-Bereuter- Blumenauer Flood Insurance Reform Act	Reduce or eliminate the long-term risk of flood damage to SRL residential structures currently insured under the NFIP

The HMGP and PDM programs offer funding for mitigation planning and project activities that address multiple natural hazard events. The FMA, RFC, and SRL programs focus funding efforts on reducing claims against the NFIP. Funding under the HMA programs is subject to availability of annual appropriations, and HMGP funding is also subject to the amount of FEMA disaster recovery assistance provided under a presidential major disaster declaration.

FEMA's HMA grants are awarded to eligible states, tribes, and territories (applicant) that, in turn, provide subgrants to local governments and communities (subapplicant). The applicant selects and prioritizes subapplications developed and submitted to them by subapplicants and submits them to FEMA for funding consideration. Prospective subapplicants should consult the office designated as their applicant for further information regarding specific program and application requirements. Contact information for the FEMA Regional Offices and State Hazard Mitigation Officers (SHMO) is available on the FEMA website (www.fema.gov).

4.3.2 Additional Mitigation Programs and Assistance

Several additional agencies including USACE, Natural Resource Conservation Service (NRCS), U.S. Geological Survey (USGS), and others have specialists on staff and can offer further information on flood hazard mitigation. The State NFIP Coordinator and SHMO are state-level sources of information and assistance, which vary among different states.

The Silver Jackets program, active in several states, is a partnership of USACE, FEMA, and state agencies. The Silver Jackets program provides a state-based strategy for an interagency approach to planning and implementing measures for risk reduction.

5 Acronyms and Definitions

5.1 Acronyms

Α

AAL Average Annualized Loss
ALR Annualized Loss Ratio
AoMI Areas of Mitigation Interest

В

BCA Benefit-Cost Analysis
BFE Base Flood Elevation

BMP Best Management Practices

C

CFR Code of Federal Regulations
COG Continuity of Government Plan
COOP Continuity of Operations Plan
CRS Community Rating System
CSLF Changes Since Last FIRM

D

DHS Department of Homeland Security
DMA 2000 Disaster Mitigation Act of 2000

E

EOP Emergency Operations Plan

F

FEMA Federal Emergency Management Agency

FIRM Flood Insurance Rate Map
FIS Flood Insurance Study
FMA Flood Mitigation Assistance

FRD Flood Risk Database FRM Flood Risk Map FRR Flood Risk Report

FY Fiscal Year

G

GIS Geographic Information System

Н

HMA Hazard Mitigation Assistance HMGP Hazard Mitigation Grant Program

IA Individual Assistance

N

NFIA National Flood Insurance Act
NFIP National Flood Insurance Program
NRCS Natural Resource Conservation Service

P

PA Public Assistance
PDM Pre-Disaster Mitigation

R

RFC Repetitive Flood Claims

Risk MAP Mapping, Assessment, and Planning

S

SFHA Special Flood Hazard Area
SHMO State Hazard Mitigation Officer

SRL Severe Repetitive Loss

U

USACE U.S. Army Corps of Engineers

USGS U.S. Geological Survey

5.2 Definitions

0.2-percent-annual-chance flood – The flood elevation that has a 0.2-percent chance of being equaled or exceeded each year. Sometimes referred to as the 500-year flood.

1-percent-annual-chance flood – The flood elevation that has a 1-percent chance of being equaled or exceeded each year. Sometimes referred to as the 100-year flood.

Annualized Loss Ratio (ALR) – Expresses the annualized loss as a fraction of the value of the local inventory (total value/annualized loss).

Average Annualized Loss (AAL) – The estimated long-term weighted average value of losses to property in any single year in a specified geographic area.

Base Flood Elevation (BFE) – Elevation of the 1-percent-annual-chance flood. This elevation is the basis of the insurance and floodplain management requirements of the NFIP.

Berm – A small levee, typically built from earth.

Cfs – Cubic feet per second, the unit by which discharges are measured (a cubic foot of water is about 7.5 gallons).

Consequence (of flood) – The estimated damages associated with a given flood occurrence.

Crest – The peak stage or elevation reached or expected to be reached by the floodwaters of a specific flood at a given location.

Dam – An artificial barrier that has the ability to impound water, wastewater, or any liquid-borne material, for the purpose of storage or control of water.

Design flood event – The greater of the following two flood events: (1) the base flood, affecting those areas identified as SFHAs on a community's FIRM; or (2) the flood corresponding to the area designated as a flood hazard area on a community's flood hazard map or otherwise legally designated.

Erosion – Process by which floodwaters lower the ground surface in an area by removing upper layers of soil.

Essential facilities – Facilities that, if damaged, would present an immediate threat to life, public health, and safety. As categorized in Hazus, essential facilities include hospitals, emergency operations centers, police stations, fire stations, and schools.

Flood – A general and temporary condition of partial or complete inundation of normally dry land areas from (1) the overflow of inland or tidal waters or (2) the unusual and rapid accumulation or runoff of surface waters from any source.

Flood Insurance Rate Map (FIRM) – An official map of a community, on which FEMA has delineated both the SFHAs and the risk premium zones applicable to the community. See also Digital Flood Insurance Rate Map.

Flood Insurance Study (FIS) Report – Contains an examination, evaluation, and determination of the flood hazards of a community, and if appropriate, the corresponding water-surface elevations.

Flood risk – Probability multiplied by consequence; the degree of probability that a loss or injury may occur as a result of flooding. Sometimes referred to as flood vulnerability.

Flood vulnerability – Probability multiplied by consequence; the degree of probability that a loss or injury may occur as a result of flooding. Sometimes referred to as flood risk.

Floodborne debris impact – Floodwater moving at a moderate or high velocity can carry floodborne debris that can impact buildings and damage walls and foundations.

Floodwall – A long, narrow concrete or masonry wall built to protect land from flooding.

Floodway (regulatory) – The channel of a river or other watercourse and that portion of the adjacent floodplain that must remain unobstructed to permit passage of the base flood without cumulatively increasing the water surface elevation more than a designated height (usually 1 foot).

Floodway fringe – The portion of the SFHA that is outside of the floodway.

Freeboard – A factor of safety usually expressed in feet above a flood level for purposes of flood plain management. "Freeboard" tends to compensate for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as wave action, bridge openings, and the hydrological effect of urbanization of the watershed (44CFR§59.1).

Hazus – A GIS-based risk assessment methodology and software application created by FEMA and the National Institute of Building Sciences for analyzing potential losses from floods, hurricane winds and storm surge, and earthquakes.

High velocity flow – Typically comprised of floodwaters moving faster than 5 feet per second.

Levee – A human-made structure, usually an earthen embankment, designed and constructed in accordance with sound engineering practices to contain, control, or divert the flow of water so as to provide protection from temporary flooding. (44CFR§59.1)

Loss ratio – Expresses loss as a fraction of the value of the local inventory (total value/loss).

Mudflow – Mudslide (i.e., mudflow) describes a condition where there is a river, flow or inundation of liquid mud down a hillside usually as a result of a dual condition of loss of brush cover, and the subsequent accumulation of water on the ground preceded by a period of unusually heavy or sustained rain. A mudslide (i.e., mudflow) may occur as a distinct phenomenon while a landslide is in progress, and will be recognized as such by the Administrator only if the mudflow, and not the landslide, is the proximate cause of damage that occurs. (44CFR§59.1)

Probability (of flood) – The likelihood that a flood will occur in a given area.

Risk MAP – Risk Mapping, Assessment, and Planning, a FEMA strategy to work collaboratively with state, local, and tribal entities to deliver quality flood data that increases public awareness and leads to action that reduces risk to life and property.

Riverine – Of or produced by a river. Riverine floodplains have readily identifiable channels.

Special Flood Hazard Area (SFHA) – Portion of the floodplain subject to inundation by the 1-percentannual or base flood.

Stafford Act – Robert T. Stafford Disaster Relief and Emergency Assistance Act, PL 100-707, signed into law November 23, 1988; amended the Disaster Relief Act of 1974, PL 93-288. This Act constitutes the statutory authority for most federal disaster response activities especially as they pertain to FEMA and FEMA programs.

Stillwater – Projected elevation that flood waters would assume, referenced to National Geodetic Vertical Datum of 1929, North American Vertical Datum of 1988, or other datum, in the absence of waves resulting from wind or seismic effects.

Stream Flow Constrictions – A point where a human-made structure constricts the flow of a river or stream.

6 Additional Resources

ASCE 7 – National design standard issued by the American Society of Civil Engineers (ASCE), *Minimum Design Loads for Buildings and Other Structures*, which gives current requirements for dead, live, soil, flood, wind, snow, rain, ice, and earthquake loads, and their combinations, suitable for inclusion in building codes and other documents.

ASCE 24-05 – National design standard issued by the ASCE, *Flood Resistant Design and Construction*, which outlines the requirements for flood resistant design and construction of structures in flood hazard areas.

National Flood Insurance Program (NFIP), Federal Emergency Management Agency (FEMA), www.floodsmart.gov

FEMA, www.fema.gov

ASCE, 2010. So, You Live Behind a Levee! Reston, VA.

FEMA Publications – available at www.fema.gov

FEMA, 1985. *Manufactured Home Installation in Flood Hazard Areas*, FEMA 85. Washington, DC, September 1985.

FEMA and the American Red Cross, 1992. *Repairing Your Flooded Home*, FEMA 234/ARC 4476. Washington, DC, August 1992.

FEMA, 1996. Addressing Your Community's Flood Problems, FEMA 309. Washington, DC, June 1996.

FEMA, 1998. Homeowner's Guide to Retrofitting, FEMA 312. Washington, DC, June 1998.

FEMA, 1999. *Protecting Building Utilities from Flood Damage*, FEMA 348. Washington, DC, November 1999.

FEMA, 1999. Riverine Erosion Hazard Areas Mapping Feasibility Study. Washington, DC, September 1999

FEMA, 2003. *Interim Guidance for State and Local Officials - Increased Cost of Compliance Coverage*, FEMA 301. Washington, DC, September 2003.

FEMA, 2000. Above the Flood: Elevating Your Floodprone House, FEMA 347. Washington, DC, May 2000.

FEMA, 2001. *Understanding Your Risks: Identifying Hazards and Estimating Losses*, FEMA 386-2. Washington, DC, August 2001.

FEMA, 2002a. *Getting Started: Building Support for Mitigation Planning*, FEMA 386-1. Washington, DC, September 2002.

FEMA, 2002b. *Integrating Manmade Hazards into Mitigation Planning*, FEMA 386-7. Washington, DC, September 2002.

FEMA, 2003a. *Developing the Mitigation Plan: Identifying Mitigation Actions and Implementing Strategies*, FEMA 386-3. Washington, DC, April 2003.

FEMA, 2003b. *Bringing the Plan to Life: Implementing the Hazard Mitigation Plan*, FEMA 386-4. Washington, DC, August 2003.

FEMA, 2004a. *Design Guide for Improving School Safety in Earthquakes, Floods, and High Winds*, FEMA 424. Washington, DC, January 2004.

FEMA, 2004b. Federal Guidelines for Dam Safety: Emergency Action Planning for Dam Owners, FEMA 64. Washington, DC, April 2004.

FEMA, 2005. *Integrating Historic Property and Cultural Resource Considerations into Hazard Mitigation Planning*, FEMA 386-6. Washington, DC, May 2005.

FEMA, 2006a. Multi-Jurisdictional Mitigation Planning, FEMA 386-8. Washington, DC, August 2006.

FEMA, 2006b. *Using the Hazard Mitigation Plan to Prepare Successful Mitigation Projects*, FEMA 386-9. Washington, DC, August 2008.

FEMA, 2006c. "Designing for Flood Levels Above the BFE," Hurricane Katrina Recovery Advisory 8, Hurricane Katrina in the Gulf Coast: Building Performance Observations, Recommendations, and Technical Guidance, FEMA 549, Appendix E. Washington, DC, July 2006.

FEMA, 2007a. *Property Acquisition Handbook for Local Communities*, FEMA 317. Washington, DC, September 2007.

FEMA, 2007b. Public Assistance Guide, FEMA 322. Washington, DC, June 2007.

FEMA, 2007c. *Using Benefit-Cost Review in Mitigation Planning*, FEMA 386-5. Washington, DC, May 2007.

FEMA, 2007d. *Design Guide for Improving Critical Facility Safety from Flooding and High Winds: Providing Protection to People and Buildings*, FEMA 543. Washington, DC, January 2007.

FEMA, 2007e. *Selecting Appropriate Mitigation Measures for Floodprone Structures*, FEMA 551. Washington, DC, March 2007.

FEMA, 2007f. Design Guide for Improving Hospital Safety in Earthquakes, Floods, and High Winds: Providing Protection to People and Buildings, FEMA 577. Washington, DC, June 2007.

FEMA, 2008. Reducing Flood Losses Through the International Codes: Meeting the Requirements of the National Flood Insurance Program, FEMA 9-0372, Third Edition. Washington, DC, December 2007.

7 Data Used to Develop Flood Risk Products

GIS base map information was acquired from the following sources:

- State of Connecticut GIS Office
- U.S. Geological Survey

Engineering study information was compiled by the U.S. Geological Survey for reaches of new detailed study, with leveraged information from effective countywide studies from FEMA. Mitigation Plans and AoMI information were acquired from local community input as well as significant input from the State of Connecticut Department of Energy and Environmental Protection.